

## REMARKS

In view of the above amendments and following remarks, reconsideration and further examination are requested.

The specification and abstract have been reviewed and revised to make editorial changes thereto and generally improve the form thereof, and a substitute specification and abstract are provided. No new matter has been added by the substitute specification and abstract.

Initially, the courtesies extended by Examiner Kenny and Examiner Cuda during the interview conducted on March 30, 2004 are greatly appreciated. During the interview, proposed amendments to claims 1 and 8 were discussed.

With regard to claim 1, Applicants' undersigned representative first proposed to amend this claim by reciting that the process-finished board send-out device is different from the unprocessed board carry-in device. This proposed amendment was believed to define around Gieskes since in the rejection of claims 1-10 as expressed in the Office Action mailed December 9, 2003, it appeared as though the Examiner was corresponding the same structure of Gieskes to both of the claimed "process-finished board send-out device" and "unprocessed board carry-in device". The Examiners expressed that such an amendment would not define around Gieskes, because in this reference conveyor 28 could be equated to the claimed "unprocessed board carry-in device"; the most upstream portion of conveyor 28, or any structure that supplies circuit boards onto conveyor 28, could be equated to the claimed "unprocessed board transfer path"; conveyor 52 could be equated to the claimed "process-finished board transfer path"; and shuttle 18 could be equated to each of the claimed "process-finished board send-out device" and "shift device", wherein "18" is different from "28".

Next during the interview was discussed a second proposed amendment for claim 1, which recited that the component-mounted board production apparatus is arranged only on one side of the unprocessed board transfer unit and the process-finished board transfer unit in a direction orthogonal to a transfer direction of the unprocessed board and the processed board, i.e. on only one side of board transfer paths. This proposed amendment was believed to define around Gieskes, because in Gieskes board production apparatus or assembly modules are provided on both sides of board transfer paths. The Examiners expressed that even though Gieskes does not disclose a board production apparatus only on one side of board transfer paths, such a limitation would not be sufficient to define

around Gieskes, because one having ordinary skill in the art would have found it obvious to modify Gieskes by having the assembly modules, i.e. board production apparatus, only be on one side of the board transfer paths depending upon engineering design choices such as a desired rate of production or space limitations.

Next during the interview was discussed a proposed amendment to claim 8, which recited that the process-finished board transfer path is different from the unprocessed board transfer path. This proposed claim was believed to define around Gieskes, because in the rejection of the Office Action mailed December 9, 2003, the Examiner apparently equated the same conveyor to both the unprocessed board transfer path and process-finished board transfer path. The Examiners expressed that this proposed amendment to claim 8 can also be read on Gieskes. Specifically, the Examiners expressed that a path can broadly be defined as nothing more than a direction in which something travels such that Figure 4 of Gieskes can be said to show the method as recited in claim 8.

Finally during the interview, a further proposed amendment to claim 8 was discussed, which basically corresponded to claim 9 rewritten in independent form. The Examiners expressed that this second proposed amendment to claim 8 appears to define around Gieskes; however, they were unable to definitely state that this claim would be allowable since this claim would require further consideration and/or search.

Claims 1 - 10 were rejected under 35 U.S.C. 102(e) as being anticipated by Gieskes. After considering this rejection, the patent to Gieskes, and the positions expressed by the Examiners during the interview conducted on March 30, 2004, claims 1-18 have been cancelled and claims 19-39 have been added.

Independent claim 19 generally corresponds to the first proposed amendment to claim 1 as discussed during the interview. In this regard, claim 19 generally differs from rejected claim 1 by reciting that the process-finished board send-out device is different from the unprocessed board carry-in device. It is appreciated that during the interview the Examiners expressed that they believe this claim can be read on Gieskes; however, for reasons to follow it is respectfully requested that the Examiners reconsider their position.

As alluded to previously, in order to read claim 19 on Gieskes, shuttle 18 would have to be equated to both the process-finished board send-out device and the shift device. It is respectfully

submitted that to equate shuttle 18 to both the process-finished board send-out device and the shift device is unreasonable. In this regard, the process-finished board send-out device and the shift device are recited in claim 19 as separate and distinct elements. Not only is it believed to be unreasonable to equate a single element in a patent to two distinct elements in a claim, but also nowhere in Gieskes is the construction of the shuttle 18 sufficiently disclosed such that it can be construed to be both a shift device and a board send-out device.

Also, assuming *arguendo* that shuttle 18 can somehow be equated to each of the process-finished board send-out device and the shift device, claim 19 requires that the process-finished board send-out device is to “carry the process-finished board **out** from the first component-mounted board production apparatus”. In Gieskes, a processed board is carried out from production apparatus or assembly module 14 prior to its being manipulated by shuttle 18. Accordingly, because shuttle 18 does not carry a process-finished board “out” from the component-mounted board production apparatus 14, it is respectfully submitted that shuttle 18 cannot reasonably be corresponded to the process-finished board send-out device as claimed.

The structure which carries the process-finished board out from the component-mounted board production apparatus 14 is conveyor 28; however, as expressed previously, conveyor 28 has been equated to the unprocessed board carry-in device, and thus cannot also be equated to the process-finished board send-out device, since claim 19 requires that the process-finished board send-out device is different from the unprocessed board carry-in device.

In view of the above it is respectfully submitted that claim 19 is allowable over any possible reasonable interpretation of Gieskes, whereby claims 19 - 26 are allowable.

Independent claim 27 generally corresponds to former claim 6, and is believed to be allowable over Gieskes for reasons analogous to those expressed above with regard to claim 19. In this regard, claim 27 also requires that the process-finished board send-out device is different from the unprocessed board carry-in device, and that the process-finished board send-out device is to carry a process-finished board “out” from the component-mounting board production device. Thus, claims 28 - 36 are also allowable.

And, new claim 37 generally corresponds to the first proposed claim 8 presented during the interview; however, claim 37 recites an unprocessed board transfer “conveyor” and a process-finished

board transfer "conveyor", as opposed to "path" so to overcome the Examiners' interpretation of the word "path". In this regard, in Gieskes the conveyor 28 from which an unprocessed board is carried into the assembly module 14 is the same conveyor 28 to which a process-finished board is carried after being processed in assembly module 14, and thus Gieskes cannot reasonably be said to disclose an unprocessed board transfer conveyor and a process-finished board transfer conveyor that are "different" from one another as required by claim 37. Similarly, Gieskes cannot reasonably be said to disclose moving the process-finished board, after leaving assembly module 14, from the process-finished board transfer conveyor (28) to the unprocessed board transfer conveyor (28), as also required by claim 37. Accordingly, claim 37 is allowable over Gieskes, whereby claims 37 - 39 are allowable.

Also, certain of the dependent claims are believed to be patentable in their own right. In this regard, claims 24, 26, 35 and 36 further define the board transferring apparatus (device) by reciting features that cannot reasonably be read on Gieskes. And, new claim 38 generally corresponds to former claim 9, the subject matter of which, during the interview, the Examiners indicated appears to be allowable over Gieskes.

If the claims are continued to be rejected over Gieskes, then the Examiner is respectfully requested to specifically explain how each claimed limitation is being read on Gieskes.

In view of the above amendments and remarks, it is respectfully submitted that the present application is in condition for allowance and an early Notice of Allowance is earnestly solicited.

If after reviewing this Amendment, the Examiner believes that any issues remain which must be resolved before the application can be passed to issue, the Examiner is invited to contact the Applicants' undersigned representative by telephone to resolve such issues.

Respectfully submitted,

Kurayasu HAMASAKI et al.

By: 

Joseph M. Gorski

Registration No. 46,500

Attorney for Applicants

JMG/edg  
Washington, D.C. 20006-1021  
Telephone (202) 721-8200  
Facsimile (202) 721-8250  
May 7, 2004

## SPECIFICATION

~~TITLE OF THE INVENTION~~**Board Transferring Apparatus And Method, And Component Mounting Apparatus**5 **TECHNICAL FIELD**

[0001] The present invention relates to a board transferring apparatus for transferring boards, e.g., printed boards or the like to a component mounting apparatus which mounts components, e.g., electronic components or the like to the boards, ~~and a board transfer method~~ ~~carried out~~performed by the board transferring apparatus, and a component mounting apparatus  
10 used with the board transferring apparatus.

**BACKGROUND ARTS**ART

[0002] In accordance with ~~the~~ widespread use of lead-wire less electronic components, namely, so-called chip components, ~~the~~ components vary in shape and size ~~late~~ly. Since an  
15 electronic circuit is constituted by combining ~~the~~such electronic components, a much higher speed and a high reliability are demanded to be secured for electronic component mounting apparatuses which fix the electronic components to printed boards.

[0003] A plurality of the electronic component mounting apparatuses of the type referred to above are generally used in order to mount the electronic components to many printed boards.  
20 Since a loading operation of the printed board takes place ~~in~~for each component mounting apparatus when a plurality of the component mounting apparatuses are employed for one board transfer path, there is a problem that a degree of increase in production efficiency lowers as compared with a degree of increase in ~~the~~a number of apparatuses to be set. ~~Supposed~~Suppose, for example, that a board loading time at each component mounting apparatus is 4 seconds and a

mounting time of all electronic components is 10 seconds, ~~for example then~~ one component mounting apparatus requires 14 ~~(=10+4)~~(10+4) seconds and two component mounting apparatuses require 9 ~~(=(10/2)+4)~~(10/2)+4) seconds to produce one complete board.

[0004] The applicant of the present invention has disclosed an invention as a technique for solving the above problem in a publication of unexamined ~~paten~~-patent application of JP, 10-256785, A. ~~The~~A constitution and ~~the~~an operation of a printed board transferring apparatus disclosed in the published application of the above JP, 10-256785, A will be described below with reference to Fig. 9.

[0005] Roughly speaking, a component mounting apparatus 1 shown in Fig. 9 comprises two mounting parts 2A, 2B arranged in series, moving devices 3A, 3B for boards to be mounted, which are set respectively to the mounting parts 2A, 2B, a carry-in device 4 for supplying unmounted boards 7 to the mounting parts 2A, 2B, and a carry-out device 5 for transferring mounted boards 8 sent out from the mounting parts 2A, 2B. Although the carry-in device 4 and the carry-out device 5 are illustrated as if arranged in parallel ~~on an equal~~in the same plane in Fig. 9 to facilitate ~~the~~a graphic representation and description, and moreover understanding, the carry-out device 5 and the carry-in device 4 are actually placed in an overlapping manner so as to be arranged on upper and lower sides to make the apparatus compact.

[0006] The moving devices 3A, 3B for boards to be mounted have loader conveyors 31A, 31B which reciprocate between the carry-in device 4 and the mounting parts 2A, 2B to supply unmounted boards 7 from the carry-in device 4 to the mounting parts 2A, 2B, and unloader conveyors 32A, 32B which reciprocate between the mounting parts 2A, 2B and the carry-out device 5 to send out mounted boards 8 from the mounting parts 2A, 2B to the carry-out device 5. Since the carry-in device 4 and the carry-out device 5 are set in an overlapping manner in an the up-down direction as mentioned above, the loader conveyors 31A, 31B move slantwise along a

first direction 10 orthogonal to a board transfer direction 9, while the unloader conveyors 32A, 32B, positioned at an equal height ~~to~~as that of the carry-out device 5, move at ~~the~~this height in a second direction 11.

[0007] The component mounting apparatus 1 constituted as above operates in a manner to be described below.

[0008] When the mounting part 2A is not operating, ~~the~~an unmounted board 7 transferred by the carry-in device 4 from ~~an~~-upstream equipment (not shown) is carried by the loader conveyor 31A into the mounting part 2A, and then all electronic components are mounted ~~onto~~to the unmounted board 7 at the mounting part 2A. ~~The~~A mounted board 8 with the components mounted thereon is carried by the unloader conveyor 32A to the carry-out device 5 and then transferred by the carry-out device 5 to ~~an~~-equipment of a next process.

[0009] If the mounting part 2A is ~~driving~~operating, the unmounted board 7 is transferred by the carry-in device 4, to pass a section of the mounting part 2A, to the mounting part 2B. When the mounting part 2B is not operating at this time, the unmounted board 7 is carried into the mounting part 2B by the loader conveyor 31B, and then all electronic components are mounted ~~to~~onto the unmounted board 7 by the mounting part 2B. ~~The~~A mounted board 8 with the components mounted thereon is sent out by the unloader conveyor 32B to the carry-out device 5 and transferred by the carry-out device 5 to ~~the~~-next process equipment.

[0010] In producing one mounted board 8 in the component mounting apparatus 1 as described above, ~~the~~a loading operation of boards to the mounting parts 2A, 2B is completed at a time irrespective of ~~the~~a number of ~~the~~set-mounting parts. In other words, boards 7 can be supplied independently to each of the mounting parts 2A, 2B because of ~~the~~-presence of the carry-in device 4 and the carry-out device 5. Given, for instance, that a board loading time and a mounting time at each of the mounting parts 2A, 2B are 4 seconds and 10 seconds, respectively,

and since ~~the~~ boards 7 can be supplied and equipped with ~~the~~ components at the same time at the mounting parts 2A, 2B, a line Tact necessary for producing one finished board becomes  $(10+4)/2$ , i.e., 7 seconds, and shortened by 2 seconds in comparison with the earlier-mentioned 9 seconds.

[0011] The invention disclosed by the published application of the above JP, 10-256785, A is aimed to provide a board transfer method whereby a production efficiency of ~~the~~an electronic component mounting apparatus can be improved by shortening ~~the~~a loading time per board sent out from ~~the~~ component mounting apparatus 1. on ~~the~~an understanding that each mounting part 2A, 2B can mount all necessary electronic components for producing one mounted board 8. However, as in recent years, a production form, ~~that~~in which a volume of production is relatively low and there are a wide variety of products to be made, is frequently practiced. Therefore, ~~the~~a condition that all of ~~the~~ electronic components are mounted by ~~the~~ one mounting part without fail is difficult to ~~hold~~maintain.

[0012] Concretely, in ~~the~~a case, for example, where ~~the~~a number of types of electronic components necessary for manufacturing one mounted board 8 is more than ~~the~~a number of types of components which one mounting part can ~~have~~provide, all ~~the~~ electronic components cannot be mounted by the one mounting part. ~~Such~~In such a case as this, there is a problem in that it is necessary to set ~~an~~ another component mounting apparatus, having ~~an~~ another constitution, ~~additionally~~ in order to mount ~~the~~ remaining components.

[0013] The present invention is devised to solve the above problems and has for its object to provide a board transferring apparatus and method, and a component mounting apparatus which can improve a production efficiency in accordance with types of boards to be produced.

## **DISCLOSURE SUMMARY OF THE INVENTION**

[0014] In accomplishing the above and other ~~aspects~~objects, a board transferring



apparatus provided according to a first aspect of the present invention transfers boards between the apparatus and a component-mounted board production apparatus, which comprises;

an unprocessed board transfer unit including an unprocessed board transfer path along which an unprocessed board, as ~~the~~ a board not yet processed by the component-mounted board production apparatus, is transferred, and an unprocessed board carry-in device which moves between the unprocessed board transfer path and the component-mounted board production apparatus, thereby carrying the unprocessed board into the component-mounted board production apparatus;

a process-finished board send-out unit including a process-finished board transfer path along which a process-finished board, as ~~the~~ a board processed by the component-mounted board production apparatus, is transferred, for carrying the process-finished board out from the component-mounted board production apparatus by moving between the process-finished board transfer path and the component-mounted board production apparatus; and

a shift device which moves between the unprocessed board transfer path and the process-finished board transfer path ~~and~~ for shifting ~~the~~ a board between the unprocessed board transfer path and the process-finished board transfer path.

[0015] At least one shift device can be equipped when a plurality of ~~the above~~ component-mounted board production apparatuses are arranged in series in a transfer direction of ~~the~~ an unprocessed board and ~~the~~ a process-finished board.

[0016] The board transferring apparatus may further comprise a controller for controlling ~~the~~ operations of the unprocessed board transfer unit, the process-finished board transfer unit and the shift device.

[0017] In a case where a plurality of ~~the~~ component-mounted board production apparatuses, for executing different processes, are arranged along the transfer direction of the

unprocessed board and the process-finished board, the shift device may be disposed between a first component-mounted board production apparatus and a second component-mounted board production apparatus for executing mutually different processes, while the controller can control the shift device to shift ~~the~~ process-finished boards carried out from the first component-mounted board production apparatus to the process-finished board transfer path, to the unprocessed board transfer path.

[0018] The ~~above~~ controller can control ~~the~~ operations of the unprocessed board transfer unit, the process-finished board transfer unit and the shift device on a basis of an arrangement of the component-mounted board production apparatus along the transfer direction and a processing program to be executed ~~to the~~ for boards.

[0019] According to a second aspect of the present invention ~~is provided~~ provided is a board transfer method which comprises:

carrying an unprocessed board, as a board not processed by a component-mounted board production apparatus, from an unprocessed board transfer path into the component-mounted board production apparatus;

sending out a process-finished board, as a processed board, to a process-finished board transfer path after being processing-processed in the component-mounted board production apparatus; and

moving the process-finished board ~~of~~ from the process-finished board transfer path to the unprocessed board transfer path.

[0020] A component mounting apparatus ~~in~~ according to a third aspect of the present invention comprises the board transferring apparatus of the ~~above~~ first aspect.

[0021] According to the board transferring apparatus of the first aspect, the board transfer method of the second aspect, and the component mounting apparatus of the third aspect of the

present invention, since the shift device is ~~equipped~~provided, it is possible to supply ~~the~~an unprocessed board from the unprocessed board transfer path to the component-mounted board production apparatus, process the unprocessed board in the component-mounted board production apparatus and transport ~~the~~a process-finished board, sent out to the process-finished board transfer path, to the unprocessed board transfer path again, ~~thereby supplying~~such that the process-finished board can be supplied from the unprocessed board transfer path to ~~the~~another component-mounted board production apparatus. A production efficiency can be improved in accordance with types of boards to be produced.

[0022] A plurality of component-mounted board production apparatuses are arranged in series in the transfer direction together with the controller which controls the shift device to transport ~~the~~a process-finished board, sent out from ~~the~~a first component-mounted board production apparatus to the process-finished board transfer path, to the unprocessed board transfer path. Therefore, various production forms for boards can be met without changing a layout in a factory including a layout of ~~the~~a board production line and incidental facilities, ~~etc and the like.~~ The production Production efficiency can hence be improved in accordance with types of boards to be produced.

[0023] Further, the controller is adapted to control ~~the~~ operations of the unprocessed board transfer unit, the process-finished board transfer unit, and the shift device based on ~~the~~an arrangement of the component-mounted board production apparatus and ~~the~~a processing program to be executed ~~to~~for the boards, whereby ~~the~~ production efficiency can be improved in accordance with kinds of boards to be produced.

[0024] According to a board transferring apparatus ~~in~~according to a fourth aspect of the present invention for transferring boards on a board transfer path and between the board transfer path and a component-mounted board production apparatus while the component-mounted board

production apparatus is disposed along the board transfer path where boards are transferred in a transfer direction, the board transferring apparatus comprises:

a board carry-in unit which moves between the board transfer path and the component-mounted board production apparatus, thereby carrying ~~the~~a board into the component-mounted board production apparatus;

a board send-out unit which moves between the board transfer path and the component-mounted board production apparatus, thereby sending ~~out~~the board from the component-mounted board production apparatus to the board transfer path;

an identifying device disposed ~~to~~on the board transfer path for identifying a carry-in propriety display part on the board indicative of whether or not the board can be carried into the component-mounted board production apparatus; and

a controller for determining whether or not the board is to be carried into the component-mounted board production apparatus on a basis of ~~the~~an identification result of the carry-in propriety display part identified by the identifying device, and controlling ~~the~~an operation of the board carry-in unit.

**[0025]** When the controller determines that the board is to be carried into the component-mounted board production apparatus on the basis of the identification result, the controller is adapted to ~~carry the board by~~have the board carry-in unit carry the board into the component-mounted board production apparatus, ~~process~~have the board processed by the component-mounted board production apparatus and have this processed board sent ~~send out the processed board~~ by the board send-out unit to the board transfer path.

**[0026]** ~~While the~~When a plurality of component-mounted board production apparatuses is~~are~~ arranged ~~by a plurality of the number~~ in series along the board transfer path, with ~~the~~an identifying device being ~~disposed~~provided corresponding to each of the component-mounted

board production apparatuses, the controller determines on ~~the a~~ basis of ~~the an~~ identification result whether or not ~~the an~~ identified board is to be carried into one of the component-mounted board production ~~apparatus apparatuses~~ and can ~~let allow~~ the identified board to be transferred along the board transfer path in the transfer direction when determining that the identified board

5 is not to be carried into the component-mounted board production apparatus.

[0027] A recognizing device may further be ~~further~~ included in the board transferring apparatus, which is disposed corresponding to a component-mounted board production apparatus arranged ~~to at~~ a trail end in the transfer direction, from among ~~the a~~ plurality of ~~the~~ component-mounted board production apparatuses, for recognizing a propriety of processing by the

10 component-mounted board production ~~apparatus apparatuses~~ for ~~the a~~ board transferred along the board transfer path.

[0028] ~~The A~~ carry-in propriety display part can be a mark preliminarily applied to the board.

[0029] According to a fifth aspect of the present invention provided is ~~provided a~~ board transfer method for transferring boards to a board transfer path, and between the board transfer path and a component-mounted board production apparatus disposed along the board transfer path, wherein ~~where~~ the boards are transferred in a transfer direction, which comprises:

15

identifying a carry-in propriety display part of ~~the a~~ board transferred along the board transfer path; and

20 determining, on ~~the a~~ basis of ~~the an~~ identification result, whether or not the board is to be carried into the component-mounted board production apparatus.

[0030] A component mounting apparatus according to a sixth aspect of the present invention is equipped with the board transferring apparatus of the ~~above~~ fourth aspect.

[0031] According to the board transferring apparatus of the fourth aspect, the board

transfer method of the fifth aspect, and the component mounting apparatus of the sixth aspect of the ~~above-described present~~ invention, since the identifying device and the controller are included, it is possible to determine whether or not ~~that the~~ a board can be moved to the component-mounted board production apparatus and, on ~~the~~ a basis of ~~the~~ this determination result, ~~to supply whether~~ the board is to be supplied from the board transfer path to the component-mounted board production apparatus. Thus, a production efficiency is improved in accordance with types of boards to be produced.

[0032] ~~While~~ When a plurality of component-mounted board production apparatuses are arranged in series in the transfer direction, with ~~the~~ an identifying device being ~~disposed~~ provided corresponding to each component-mounted board production apparatus, the controller determines ~~the~~ a carry-in propriety ~~to for~~ each component-mounted board production apparatus and controls ~~the~~ supply of boards, on ~~the~~ a basis of ~~the~~ this determination result, from the board transfer path to each component-mounted board production apparatus. Various production forms for boards can be met without greatly changing ~~the~~ a layout in ~~the~~ a factory including ~~the~~ a layout of ~~the~~ a board production line and incidental facilities, ~~etc~~ and the like. ~~The~~ Production efficiency can be improved in accordance with kinds of boards to be produced.

[0033] A recognizing device is installed corresponding to a component-mounted board production apparatus ~~of~~ at a trail end when a plurality of component-mounted board production apparatuses are arranged, so that ~~the~~ propriety of processing ~~at the~~ for each component-mounted board production apparatus is recognized by the recognizing device. Therefore, boards can be prevented from being sent out in a state without being processed ~~to at~~ a next ~~process~~ component-mounted board protection apparatus.

**BRIEF DESCRIPTION OF THE DRAWINGS**

[0034] These and other aspects and features of the present invention will become clear from the following description taken in conjunction with the preferred embodiments thereof with reference to the accompanying drawings, in which:

5 [0035] Fig. 1 is a diagram showing ~~the~~a constitution of a component mounting apparatus according to a first embodiment of the present invention;

[0036] Fig. 2 is a front view of the component mounting apparatus shown in Fig. 1;

[0037] Fig. 3 is a diagram showing ~~the~~ structure of an unprocessed board carry-in device included in the component mounting apparatus shown in Fig. 1;

10 [0038] Fig. 4 is an oblique view showing ~~the~~ structure of a component supply/mounting machine included in the component mounting apparatus shown in Fig. 1;

[0039] Fig. 5 is a diagram showing ~~the~~ structure of a process-finished board send-out device included in the component mounting apparatus shown in Fig. 1;

15 [0040] Fig. 6 is an oblique view showing ~~the~~ structure of a shift device included in the component mounting apparatus shown in Fig. 1;

[0041] Fig. 7 is a diagram of a component mounting apparatus comprising two component mounting apparatuses of Fig. 1 arranged in series;

[0042] Fig. 8 is a diagram of a component mounting apparatus comprising six component mounting apparatuses of Fig. 1 arranged in series;

20 [0043] Fig. 9 is a diagram showing ~~the~~ structure of a conventional component mounting apparatus;

[0044] Fig. 10 is a diagram showing ~~the~~a constitution of a component mounting apparatus according to a second embodiment of the present invention;

[0045] Fig. 11 is a side view of the component mounting apparatus shown in Fig. 10;

[0046] Fig. 12 is an oblique view showing ~~the~~ structure of a component supply/mounting machine included in the component mounting apparatus shown in Fig. 10;

[0047] Fig. 13 is a diagram showing ~~the~~ structure of a board carry-in device included in the component mounting apparatus shown in Fig. 10;

5 [0048] Fig. 14 is a diagram showing ~~the~~ structure of a board send-out device included in the component mounting apparatus shown in Fig. 10;

[0049] Fig. 15 is a diagram for explaining a component mounting operation ~~carried-out~~ performed by a component mounting apparatus constituted of four component mounting apparatuses of Fig. 10 arranged in series;

10 [0050] Fig. 16 is a diagram for explaining a component mounting operation ~~carried-out~~ performed by a component mounting apparatus constituted of four component mounting apparatuses of Fig. 10 arranged in series; and

[0051] Fig. 17 is a diagram for explaining a component mounting operation ~~carried-out~~ performed by a component mounting apparatus constituted of four component mounting apparatuses of Fig. 10 arranged in series.

**BEST MODE FOR CARRYING OUT THE INVENTION DETAILED DESCRIPTION**  
**OF THE PREFERRED EMBODIMENTS**

20 [0052] A board transferring apparatus, ~~and~~ a board transfer method executed by the board transferring apparatus, and a component mounting apparatus equipped with the board transferring apparatus which are embodiments of the present invention will be described hereinbelow with reference to the drawings. It is to be noted that like parts are designated by like reference numerals ~~through~~ throughout the drawings.

[0053] A printed board will be given as an example of a board, that is, transfer object, in



the board transferring apparatus in a first and a second embodiments below, and a component supply/mounting machine for supplying and mounting electronic components, as an example of components, onto the printed board will be exemplified as one of devices having functions exerted by a component-mounted board production apparatus attached to the board transferring apparatus in the first and second embodiments. However, the component-mounted board production apparatus and the board are not limited to the above and, the component-mounted board production apparatus can be, e.g., a printing apparatus for printing a solder paste to boards, a reflow apparatus for melting the solder paste to thereby ~~soldering~~ soldering solder components, or the like, and eventually the board can be, e.g., a board before having the solder paste printed, a board with the solder paste and components set, or the like. It is to be noted that, while the printing apparatus and the reflow apparatus are often normally constituted singly, the first and the second embodiments to be described below are directed to an electronic component mounting equipment which is ~~normally used by a plurality of the number~~ employs such plural apparatus.

## FIRST EMBODIMENT

[0054] In Figs. 1 and 2 is shown a component mounting apparatus 101 which is provided with a board transferring apparatus 120 according to the present first embodiment, and which also includes a component supply/mounting machine 110 for receiving ~~the~~ a supply of an unmounted ~~board~~ boards 7 from the board transferring apparatus 120, mounting components onto these boards and then sending out a mounted board 8 with electronic components mounted thereon, after ~~the~~ this mounting, to the board transferring apparatus 120, and a controller 180 for controlling operations of the board transferring apparatus 120 and the component supply/mounting machine 110. In the present first embodiment, an example of unprocessed boards corresponds to the above unmounted board 7, and an example of process-finished boards

corresponds to the above mounted board 8. In ~~the unmounted board~~ boards 7 are included one having one circuit exerting one function formed ~~to on one sheet side~~, and one having a plurality of circuits each exerting the same function formed ~~to on one sheet side~~.

[0055] Although the controller 180 is indicated to be separately arranged from the component mounting apparatus in Fig. 1, ~~etc.~~, the controller may be arranged inside the component mounting apparatus or can be arranged for every part constituting the component mounting apparatus.

[0056] Moreover, although an unprocessed board transfer path 1211 and a process-finished board transfer path 1221 to be described below are illustrated in Figs. 1, 7 and 8 as if arranged in parallel ~~on in the same plane~~ to facilitate ~~the a~~ graphic expression and understanding of the invention, actually, the unprocessed board transfer path 1211 and the process-finished board transfer path 1221 are disposed overlapping one another in a vertical direction as shown in Fig. 3 from ~~the a~~ viewpoint of saving a space in the board transferring apparatus 120 of the present first embodiment. Needless to say, the arrangement of the unprocessed board transfer path 1211 and the process-finished board transfer path 1221 is not limited to the above-described positional relationship and can be made parallel ~~on in the same plane~~ as shown in Fig. 1, and the like. In addition, although the process-finished board transfer path 1221 is set to ~~the an~~ upside and the unprocessed board transfer path 1211 is placed below the process-finished board transfer path in the present first embodiment as will be discussed later, ~~the this~~ arrangement may be inverted ~~upside down~~.

[0057] The component supply/mounting machine 110 is a high-speed type machine ~~type~~ of ~~the a~~ so-called rotary form and comprises, as shown in Fig. 4, a component hold/mounting unit 111, a component supply unit 112 for supplying electronic components to the component hold/mounting unit 111, an XY-table 113 movable in XY-directions orthogonal to each other for

loading ~~the~~an unmounted board 7 thereon, and a board supply/send unit 114 for supplying the unmounted board 7 to the XY-table 113 and sending ~~out~~ the unmounted board 7 from the XY-table 113.

[0058] The component hold/mounting unit 111 has a rotating device 1111 and a rotary part 1112 intermittently rotatable by the rotating device 1111 by ~~every~~a predetermined angle. To a periphery of the rotary part 1112 are set, so as to move ~~movably~~ up and down, a plurality of component hold/lift parts 1113 spaced from one another at equal intervals and each having a component hold member 1114 fitted to a leading end for holding ~~the~~an electronic component, for example, by suction. The thus-constituted component hold/mounting unit 111 will not move in the XY-directions.

[0059] The component supply unit 112 is comprised of component supply parts 1121 with reels 1123 installed for each kind of electronic ~~components~~component 115, which ~~let off~~ unwinds ~~tapes, storing electronic components 115, wound to the respective reels 1123~~ from the reels 1123, ~~storing the electronic components 115~~ thereby supplying respective electronic components 115, and a moving device 1122 having ~~the~~ component supply parts 1121 set thereto for moving the component supply parts 1121 in the X direction to make the component hold/mounting unit 111 hold desired electronic components 115.

[0060] The board supply/send unit 114 has a board transfer passage 1141, and a driving device for transfer 1142 for transferring ~~the~~an unmounted board 7 and mounted board 8 along the board passage 1141. The board transfer passage 1141 is formed of a fixed side rail 125 and a movable side rail 126 extending in parallel along a transfer direction 124 of the unmounted board 7 and mounted board 8. The board transfer passage can be fitted to ~~the~~ boards 7, 8 of any size by moving the movable side rail 126 in a breadth direction of the boards 7, 8. The fixed side rail 125 and the movable side rail 126 are provided with belt conveyors capable of supporting

opposite side edge portions of ~~the~~ respective boards 7, 8. The boards 7, 8 are transferred in the transfer direction 124 by driving each belt conveyor ~~by~~ via the driving device 1142 for transfer.

[0061] The above-described component hold/mounting unit 111, the component supply unit 112, the XY-table 113, and the board supply/send unit 114 are each connected to the controller 180 and controlled in operation by the controller 180.

[0062] The electronic components 115 are supplied and mounted by operations, to be described below, in the component supply/mounting machine 110 constituted as above. Specifically, ~~the~~ unmounted board 7 is first placed on the XY-table 113 by the board supply/send unit 114. The unmounted board 7 is moved by the XY-table 113 to below the rotary part 1112 and is further positioned to make a mounting preparation position at the rotary part 1112 agree with a mounting position on the unmounted board 7. In the meantime, the component supply part 1121, which is to supply ~~the~~ a desired electronic component 115, is positioned by the moving device 1122 to a component hold position where the component hold member 1114 ~~holds~~ is to hold the electronic component 115 received from the component supply part 1121. The component hold/lift part 1113 moves down and the component hold member 1114 holds the electronic component 115. After ~~the~~ this holding, the component hold/lift part 1113 moves up and the rotary part 1112 is rotated by the rotating device 1111 to arrange the component hold/lift part 1113 to the mounting preparation position for mounting the held electronic component 115 to the board 7. Then, the component hold/lift part 1113 is moved down, thereby mounting the electronic component 115 to the mounting position of the board 7. The component hold/lift part 1113 moves up after ~~the~~ this mounting and is disposed again to the component hold position by ~~the~~ rotation of the rotary part 1112.

[0063] Electronic components 115 are sequentially mounted by each of the component hold members 1114 onto the unmounted board 7 through a repetition of the above operations.

[0064] While the component supply/mounting machine 110 in the present first embodiment is ~~the~~ a high-speed type machine ~~type~~ of the so-called rotary form, the machine is not limited to this and various known component supply/mounting machines, for example, a so-called ~~multifunction~~ multi-function type, in which a mounting head part with the component hold members 1114 can freely move in ~~the~~ XY-directions and can supply components also from trays, and the like, can be adopted.

[0065] The board transferring apparatus 120 will be described next.

[0066] The board transferring apparatus 120 is comprised of an unprocessed board transfer unit 121, a process-finished board send-out unit 122, and a shift device 123.

[0067] The unprocessed board transfer unit 121 is equipped with the unprocessed board transfer path 1211 for transferring unmounted boards 7 to be processed by the component supply/mounting machine 110, and also with an unprocessed board carry-in device 1212 which moves between the unprocessed board transfer path 1211 and the component supply/mounting machine 110 for carrying the unmounted ~~board~~ boards 7 into the component supply/mounting machine 110. The unprocessed board transfer path 1211 is formed of a fixed side rail 125 and a movable side rail 126 extending in parallel along the transfer direction 124 of the unmounted boards 7 and mounted boards 8, functioning as a bypass line of the above board transfer passage 1141. The unprocessed board transfer path 1211 can be conformed to unmounted boards 7 of various sizes by moving the movable side rail 126 in ~~the~~ a breadth direction of the unmounted boards 7. A belt conveyor is set to each of the fixed side rail 125 and the movable side rail 126, which is capable of supporting opposite side edge portions of the unmounted board 7. ~~The~~ Each unmounted board 7 is transferred in the above transfer direction 124 by driving each belt conveyor by a driving device 1213 for transferring unmounted boards.

[0068] The unprocessed board carry-in device 1212 has, as shown in Fig. 3, a skew board

hold part 12121 and a drive part 12122. As is described before and as is clear from Fig. 3, in the first embodiment, since the unprocessed board transfer path 1211 and the process-finished board transfer path 1221 are arranged overlapping one another in the vertical direction, and moreover, the process-finished board transfer path 1221 and the board transfer passage 1141 are arranged to be the same height, the drive part 12122 reciprocates the skew board hold part 12121 slantwise between the unprocessed board transfer path 1211 and the board transfer passage 1141. A sensor 12123, e.g., a limit sensor, a proximity sensor or the like, for detecting that the skew board hold part 12121 is positioned at the unprocessed board transfer path 1211, is ~~installed~~ provided in the first embodiment. An arrangement position of the skew board hold part 12121 is determined by the controller 180 based on a signal supplied from the sensor 12123 to the controller 180.

**[0069]** The drive part 12122 is constructed ~~in from~~ a structure with including a ball screw in the present first embodiment, having a motor 121221 corresponding to a driving source being controlled in operation by the controller 180. The skew board hold part 12121 including the above fixed side rail 125 and the movable side rail 126 forms part of the unprocessed board transfer path 1211, when positioned at the unprocessed board transfer path 1211, and forms part of the board transfer passage 1141 when positioned at the board transfer passage 1141.

**[0070]** The unprocessed board carry-in device 1212 of the above constitution operates in a manner as will be described hereinbelow. The skew board hold part 12121 is normally arranged ~~to at~~ at the unprocessed board transfer path 1211. When it is necessary to carry ~~the a~~ transferred unmounted board 7 to the component supply/mounting machine 110, the unmounted board 7 is held between the fixed side rail 125 and the movable side rail 126 of the skew board hold part 12121 and shifted to the board transfer passage 1141 by the drive part 12122. ~~The A~~ mounting operation is ~~carried out to~~ performed for the unmounted board 7 carried to the board transfer passage 1141. Meanwhile, the skew board hold part 12121 returns to the unprocessed

board transfer path 1211 after the unmounted board 7 is carried to the board transfer passage 1141. When it is not necessary to carry the unmounted board 7 to the component supply/mounting machine 110, the unmounted board 7 passes the skew board hold part 12121.

[0071] The process-finished board send-out unit 122 has the process-finished board transfer path 1221 for transferring mounted boards 8 processed by the component supply/mounting machine 110 and, a process-finished board send-out device 1222 which moves between the process-finished board transfer path 1221 and the component supply/mounting machine 110 to send ~~the~~ a mounted board 8 from the component supply/mounting machine 110 to the process-finished board transfer path 1221. Similar to the above unprocessed board transfer path 1211, the process-finished board transfer path 1221 is constituted of a fixed side rail 125 and a movable side rail 126 extending in parallel along the transfer direction 124, thereby functioning as a bypass line of the board transfer passage 1141. The process-finished board transfer path can be suited to mounted boards 8 of various sizes by moving the movable side rail 126 in ~~the~~ a breadth direction of the boards 8. The fixed side rail 125 and the movable side rail 126 are equipped with belt conveyors that can support opposite side edge portions of the mounted board 8, and therefore the board 8 is transferred in the transfer direction 124 by driving each of the belt conveyors ~~by~~ via a driving device 1223 for transferring completely mounted boards.

[0072] The process-finished board send-out device 1222 has, as indicated in Fig. 5, a board hold part 12221 and a drive part 12222. The drive part 12222 reciprocates the board hold part 12221 between the process-finished board transfer path 1221 and the board transfer passage 1141. In the present first embodiment, a sensor 12223, for instance, a limit switch, a proximity sensor or the like is set for detecting that the board hold part 12221 is positioned at the process-finished board transfer path 1221, so that an arrangement position of the board hold part 12221 is

determined by the controller 180 on ~~the~~ a basis of a signal supplied from the sensor 12223 to the controller 180.

[0073] The drive part 12222 is formed ~~in~~ from a structure ~~with~~ including a ball screw in the first embodiment. A motor 122221 corresponding to a driving source is controlled in operation by the controller 180. The board hold part 12221 with the fixed side rail 125 and the movable side rail 126 forms part of the process-finished board transfer path 1221 when positioned at the process-finished board transfer path 1221, and forms part of the board transfer passage 1141 when positioned at the board transfer passage 1141.

[0074] The process-finished board send-out device 1222 thus constituted operates as follows. The board hold part 12221 is normally arranged ~~to~~ at the process-finished board transfer path 1221, and is moved by the drive part 12222 from the process-finished board transfer path 1221 to the board transfer passage 1141 when ~~the~~ a mounted board 8 is to be carried out from the component supply/mounting machine 110. After disposed to the board transfer passage 1141, the board hold part 12221 holds the mounted board 8 between the fixed side rail 125 and the movable side rail 126 of the board hold part 12221, and is subsequently moved from the board ~~path-transfer~~ passage 1141-1141 to the process-finished board transfer path 1221. The mounted board 8 sent to the process-finished board transfer path 1221 is transferred along the process-finished transfer path 1221 in the transfer direction 124 by the driving device 1223 for transferring process-finished boards.

[0075] The shift device 123, which is one of characteristic features constituting the board transferring apparatus 120 of the first embodiment, will be described now.

[0076] The shift device 123 has, as indicated in Fig. 6, a path change part 1231 and a drive part 1232. The drive part 1232 reciprocates the path change part 1231 up and down between the process-finished board transfer path 1221 and the unprocessed board transfer path



1211. According to the present first embodiment, a sensor 1233, e.g., a limit switch, a proximity sensor or the like is installed ~~to~~at each of the process-finished board transfer path 1221 and the unprocessed board transfer path 1211, whereby an arrangement position of the path change part 1231 is determined by the controller 180 based on a signal supplied from ~~the~~a corresponding sensor 1233 to the controller 180.

[0077] The drive part 1232 is of a structure ~~with~~having an air cylinder in this first embodiment. The air cylinder, corresponding to a driving source, is controlled in operation by the controller 180. The path change part 1231 having the above fixed side rail 125 and movable side rail 126 forms part of the process-finished board transfer path 1221 when positioned at the process-finished board transfer path 1221, and forms part of the unprocessed board transfer path 1211 when positioned at the unprocessed board transfer path 1211.

[0078] Since the process-finished board transfer path 1221 and the unprocessed board transfer path 1211 are arranged ~~to the~~at an upper side and ~~the~~lower side respectively, the path change part 1231 is moved in ~~the~~an up-down direction by the drive part 1232. Needless to say, however, a move direction of the path change part 1231 is not limited to this. That is, it is enough for the path change part 1231 to move between the process-finished board transfer path 1221 and the unprocessed board transfer path 1211.

[0079] Although the shift device 123 normally transports ~~the~~a mounted board 8 from the process-finished board transfer path 1221 to the unprocessed board transfer path 1211, the shift device can transfer ~~the~~an unmounted board 7 from the unprocessed board transfer path 1211 to the process-finished board transfer path 1221.

[0080] Also, while the shift device 123 shifts one board 8, 7 ~~in~~during one shift operation, the shift device is not restricted to this form of operation and can be adapted to shift a plurality of boards 8, 7 ~~in~~during one shift operation, for example, by constituting the path change part 1231

so that the plurality of boards 8, 7 can be aligned in a longitudinal direction along the transfer direction 124. The path change part 1231 for moving the plurality of boards 8, 7 is not limited to the above structure and can be configured to hold, e.g., the boards 8, 7 in layers in a thickness direction of the boards.

5 [0081] Although the shift device 123 of the above constitution will be detailed as to its operation of mounting components, the shift device 123 itself operates roughly in a manner as will be described below. For example, when it is necessary to move ~~the processed~~ a mounted board 8 to the unprocessed board transfer path 1211 while the path change part 1231 is positioned at the process-finished board transfer path 1221, the path change part 1231 is moved  
10 by the drive part 1232 from the process-finished board transfer path 1221 to the unprocessed board transfer path 1211 after holding the mounted board 8 between the fixed side rail 125 and the movable side rail 126 of the path change part 1231. The mounted board 8 sent into the unprocessed board transfer path 1211 is transferred by the driving device 1213 ~~for transferring~~  
unmounted boards along the unprocessed board transfer path 1211 in the transfer direction 124.

15 [0082] One component mounting apparatus 101 is ~~constructed~~ provided in the above-discussed constitution. A further modification can be formed as will be described below.

[0083] Specifically, a plurality of component mounting apparatuses 101-1, 101-2, ... may be arranged in the transfer direction 124 as in a component mounting apparatus 102 shown in Fig. 7. In this case, ~~the above~~ shift devices 123 can be installed ~~to the~~ at respective component  
20 mounting apparatuses 101-1, 101-2, ... or one shift device 123 can be installed for every plurality of component mounting apparatuses 101. In other words, at least one shift device 123 is satisfactory.

[0084] In ~~the~~ a case where a plurality of ~~the~~ component-mounted board production apparatuses for carrying out different processes ~~from~~ relative to each other are arranged in the

transfer direction 124, ~~the above~~ shift device 123 may be interposed between a first component-mounted board production apparatus and a second component-mounted board production apparatus, which ~~carry out~~ perform different processes ~~from~~ relative to each other. For example, when a plurality of, e.g., six component mounting apparatuses 101-1 to 101-6 are arranged in the transfer direction 124 as in a component mounting apparatus 103 of Fig. 8, and types of components to be mounted by the component mounting apparatuses 101-1 to 101-3 and by the component mounting apparatuses 101-4 to 101-6 are ~~made different,~~ in other words, when part of all components are to be mounted by the component mounting apparatuses 101-1 to 101-3, and the remaining components are to be mounted by the component mounting apparatuses 101-4 to 101-6, to one unmounted board 7, the shift device 123 can be arranged between the component mounting apparatus 101-3 and the component mounting apparatus 101-4.

[0085] A component mounting operation ~~is performed by~~ the above-discussed component mounting apparatus will be ~~depicted~~ described hereinbelow with the use of the component mounting apparatus 102 in the constitution having two component mounting apparatuses 101-1, 101-2 arranged in series along the transfer direction 124 as shown in Fig. 7 as an example. A component mounting operation ~~to the~~ for unmounted boards 7 at the component supply/mounting machine ~~110~~ (110-1, 110-2) in each component mounting apparatus ~~101~~ (101-1, 101-2) is identical to the conventional one and will therefore be briefly described.

[0086] All ~~operations~~ performances of the component mounting operation are controlled by the controller 180. More specifically, the controller 180 has a program stored therein in relation to the component mounting operation such as a relationship between mounting positions on ~~the~~ unmounted boards 7 and electronic components 115 to be mounted to the mounting positions, a mounting order, ~~etc~~ and the like. The controller 180 controls ~~the~~ operation of the component supply/mounting ~~machine 110~~ machines (110-1, 110-2) and moreover controls ~~the~~

operation of the unprocessed board transfer unit 121 including the unprocessed board carry-in device 1212, the process-finished board send-out unit 122 including the process-finished board send-out device 1222, and the shift device 123.

[0087] In the description below, unmounted boards 7 transferred from ~~the~~an upstream side of the component mounting apparatus 102 are all identical boards.

[0088] ~~The~~An unmounted board 7 transferred on the unprocessed board transfer path 1211 by the driving device 1213, for transferring unprocessed boards from the upstream side of the component mounting apparatus 102, is sent into the skew board hold part 12121 of the unprocessed board carry-in device ~~1212~~ (1212-1, 1212-2). Regarding ~~the~~a carry-in operation, the controller 180 confirms an arrangement position of the skew board hold part 12121 on ~~the~~a basis of ~~the~~a signal of the sensor 12123, and permits the unmounted board 7 to enter the skew board hold part 12121 as described ~~before~~above when the skew board hold part is positioned at the unprocessed board transfer path 1211. On the other hand, unless the skew board hold part 12121 is positioned ~~to~~at the unprocessed board transfer path 1211, the controller 180 controls ~~the~~ operation of the driving device 1213 for transferring unprocessed boards, thereby temporarily stopping the unmounted board 7 ~~to~~at a stop region 1214 located immediately before the unprocessed board carry-in device ~~1212~~ (1212-1, 1212-2). The controller permits the unmounted board 7 to enter after the skew board hold part 12121 is disposed ~~to~~at the unprocessed board transfer path 1211.

[0089] When the unmounted board 7 advances to the skew board hold part 12121, moreover, the controller 180 determines whether or not the unmounted board 7 can be sent into the component supply/mounting machine 110-1 of the component mounting apparatus 101-1 based on factors such as ~~the~~ presence of the unmounted board 7 on the XY-table 113, the fact that the component supply/mounting machine 110-1 remains at rest, ~~etc~~ and the like.

[0090] When ~~the~~-sending is decided to be possible, the skew board hold part 12121 holding the unmounted board 7 moves to the board transfer passage 1141 from the unprocessed board transfer path 1211. The unmounted board 7 of the skew board hold part 12121, after reaching the board transfer passage 1141 is transferred along the board transfer passage 1141, loaded on the XY-table 113 disposed at the board transfer passage 1141, positioned to a predetermined position and fixed.

[0091] Meanwhile, if ~~the~~-sending of the unmounted board 7 into the component supply/mounting machine 110-1 of the component mounting apparatus 101-1 is determined to be impossible, the controller 180 controls the driving device 1213 for transferring unprocessed boards, thereby passing and transferring the unmounted board 7 along the unprocessed board transfer path 1211 through the skew board hold part 12121, located ~~to~~-at the unprocessed board transfer path 1211, and through the path change part 1231, which is positioned ~~to~~-at the unprocessed board transfer path 1211, of the shift device 123-1 of the component mounting apparatus 101-1. The unmounted board 7 is transferred to the stop region 1214 of the component mounting apparatus 101-2 of a next stage. However, when ~~the~~-supplying of the unmounted board 7 to the component mounting apparatus 101-2 is forbidden, that is, when the component mounting apparatus 101-1 and the component mounting apparatus 101-2 are programmed to mount different electronic components, the unmounted board 7 is kept waiting at the skew board hold part 12121 until ~~the~~-sending of the unmounted board 7 to the component supply/mounting machine 110-1 is allowed.

[0092] If ~~the~~-sending of the unmounted board 7 to the component mounting apparatus 101-1 is impossible-~~as above~~, whether the unmounted board 7 is to be transferred to the component mounting apparatus 101-2 of the next stage or is to be kept waiting, ~~in other words~~, ~~the~~-operation of the unprocessed board carry-in device 1212 is conformed to the mounting

program stored in the controller 180 on the basis of the constitution of the component mounting apparatus, ~~the~~ a number of electronic components to be mounted and ~~the~~ an arrangement position of the shift device 123 as will be described in detail later.

[0093] ~~The~~ A component mounting operation ~~to~~ for the unmounted board 7 is performed when the unmounted board 7 can be carried to the component supply/mounting machine 110-1 and can be disposed to below ~~the~~ rotary part 1112 of ~~the~~ component hold/mounting unit 111 by ~~the~~ XY-table 113 as described above. Concretely, the unmounted board 7 on the XY-table 113 is positioned as described earlier so that ~~the~~ a mounting position on the unmounted board 7 agrees with ~~the~~ a mounting preparation position of the rotary part 1112, and furthermore, ~~the~~ component supply part 1121 is positioned by the moving device 1122 to the component hold position where the component hold member 1114 is to hold ~~the~~ an electronic component 115 supplied from the component supply part 1121. After the component hold member 1114 holds the electronic component 115 at the component hold position, the rotary part 1112 rotates to the mounting preparation position, then the electronic component 115 is mounted to the mounting position of the unmounted board 7. After ~~the~~ this mounting, the component hold member 1114 moves up and is positioned again to the component hold position by ~~the~~ rotation of the rotary part 1112. Electronic components 115 are sequentially mounted to ~~the~~ mounting positions on the unmounted board 7 by ~~the~~ component hold members 1114 of the rotary part 1112, respectively, in this manner.

[0094] After all of predetermined electronic components 115 are mounted, ~~the~~ mounted board 8 is ~~taken out~~ removed from the XY-table 113 to the board supply/send unit 114, and is further moved to and held by the board hold part 12221 of the process-finished board send-out device 1222 located at the board transfer passage ~~114~~ 1141.

[0095] The board hold part 12221 holding the mounted board 8 is moved by the drive

part 12222 from the board transfer passage 1141 to the process-finished board transfer path 1221.

The mounted board 8 moved to the process-finished board transfer path 1221 is transferred along the process-finished board transfer path 1221 in the transfer direction 124 by the driving device 1223 ~~for transferring completely mounted boards of the process-finished board send out device 1222~~ and sent to the path change part 1231 of the shift device 123.

[0096] When there are boards 7 or 8 transferred along the process-finished board transfer path 1221 from ~~the~~ an upstream side of the component mounting apparatus 101-1, the board hold part 12221 located ~~to~~ at the process-finished board transfer path 1221 lets these boards 7, 8 alike pass towards ~~the~~ a downstream side of the component mounting apparatus 101-1.

[0097] In ~~the~~ a case where the program in the controller 180 is constructed so as to change the path change part 1231, which is positioned at the process-finished board transfer path 1221 and to which ~~the~~ a mounted board 8 is carried from the process-finished board transfer path 1221 to the unprocessed board transfer path 1211, the controller 180 makes the path change part 1231 hold the mounted board 8 and then drives the drive part 1232 of the shift device 123 to move the path change part 1231 from the process-finished board transfer path 1221 to the unprocessed board transfer path 1211. The mounted board 8 shifted to the unprocessed board transfer path 1211 is sent by the driving device 1213 ~~for transferring unprocessed boards of the unprocessed board transfer unit 121~~ to the stop region 1214 in the component mounting apparatus 101-2. Regarding the mounted board 8 carried into the stop region 1214 of the component mounting apparatus 101-2, control and operation similar to the control and operation which is performed when the unmounted board 7 is sent to the component mounting apparatus 101-1 described above, are performed.

[0098] On the other hand, when it is not necessary to move the path change part 1231 from the process-finished board transfer path 1221 to the unprocessed board transfer path 1211,

the path change part 1231 is left as it is positioned at the process-finished board transfer path 1221 to transfer ~~the~~a transferred mounted board 8 to the component mounting apparatus 101-2.

[0099] As described hereinabove, in the component mounting apparatuses 101, 102 of the present first embodiment, ~~the~~a path for sending out mounted boards 8 can be switched to the process-finished board transfer path 1221 or to the unprocessed board transfer path 1211. Whether or not to move ~~the~~a mounted board 8 by the shift device 123 from the process-finished board transfer path 1221 to the unprocessed board transfer path 1211 is, as will be detailed below, pursuant to the mounting program stored in the controller 180 on the basis of the constitution of the component mounting apparatus, the number of electronic components to be mounted and the arrangement position of the shift device 123.

[00100] Controlling ~~the~~ operation of the unprocessed board carry-in device 1212 and the shift device 123 according to the aforementioned mounting program will be ~~depicted~~described in detail.

[00101] Following operation is ~~carried out~~performed in a case of completely mounting all of electronic components to be mounted to a printed board, to be produced, by one component mounting apparatus 101. Specifically, a first unmounted board 7 transferred along the unprocessed board transfer path 1211 is supplied to the component supply/mounting machine 110-1 by the unprocessed board carry-in device 1212-1, where ~~the~~a mounting operation is ~~carried out~~performed. A second unmounted board 7 transferred along the unprocessed board transfer path 1211 during the mounting operation passes the skew board hold part 12121 of the unprocessed board carry-in device 1212-1 because the component mounting apparatus 101-1 is in the middle of the mounting operation, and then is transferred to the unprocessed board carry-in device 1212-2 of the component mounting apparatus 101-2 of the next stage. The second unmounted board is supplied to the component supply/mounting machine 110-2 by the



unprocessed board carry-in device 1212-2 to be subjected to ~~the~~ a mounting operation.

[00102] After all components are mounted to the first unmounted board 7 by the component supply/mounting machine 110-1, ~~the~~-mounted board 8 is sent out by the process-finished board send-out device 1222-1 to the process-finished board transfer path 1221, and transferred along the process-finished board transfer path 1221 to a next process. A representative example of the next process is a soldering ~~apparatus operation~~ or the like. Since the component supply/mounting machine 110-1 becomes able to accept an unmounted board 7 after the mounted board 8 is sent out, a third unmounted board 7 is supplied by the unprocessed board carry-in device 1212-1 to the component supply/mounting machine 110-1.

[00103] Similarly, after all components are mounted to the second unmounted board 7 by the component supply/mounting machine 110-2, ~~the~~-this mounted board 8 is sent out by the process-finished board send-out device 1222-2 to the process-finished board transfer path 1221, and transferred along the process-finished board transfer path 1221 to the ~~above~~-above-mentioned next process. The component supply/mounting machine 110-2 can consequently accept ~~the~~ supply of a fourth unmounted board 7.

[00104] In ~~the~~ a case where all of ~~the~~ electronic components to be mounted to ~~the~~ a printed board to be produced are mounted by ~~the~~ a single component mounting apparatus 101 as described above, ~~the~~-this mounted board 8 is not shifted by the shift device 123, but is sent out from the process-finished board transfer path 1221 in the same manner as in the related art. Therefore, with ~~the~~ a plurality of component mounting apparatuses 101-1, 101-2 arranged as shown in Fig. 7, a production efficiency can be improved by sending out ~~the~~-mounted boards 8 from ~~the~~-respective component mounting apparatuses 101-1, 101-2.

[00105] On the other hand, if all of ~~the~~ electronic components to be mounted to ~~the~~ a printed board to be produced are not completely mounted by one component mounting apparatus,

for example, when part of the electronic components are mounted by the component mounting apparatus 101-1 and the remaining electronic components are mounted by the component mounting apparatus 101-2, thereby producing one printed board, following operation is carried out performed. A first unmounted board 7 transferred along the unprocessed board transfer path

5 1211 is supplied by the unprocessed board carry-in device 1212-1 to the component supply/mounting machine 110-1, and ~~the~~ a mounting operation is conducted. After components are mounted to the first unmounted board 7, ~~the~~ a mounted board 8 is carried out by the process-finished board send-out device 1222-1 to the process-finished board transfer path 1221, then moved by the shift device 123 from the process-finished board transfer path 1221 to the  
10 unprocessed board transfer path 1211 and supplied by the unprocessed board carry-in device 1212-2 of the component mounting apparatus 101-2 to the component supply/mounting machine 110-2. After the remaining components are mounted to the mounted board 8 by the component supply/mounting machine 110-2, the mounted board 8 is sent out by the process-finished board send-out device 1222-2 from the component supply/mounting machine 110-2 to the process-  
15 finished board transfer path 1221, and transferred along the process-finished board transfer path 1221 to ~~the~~ a next process.

[00106] Since ~~the~~ use of the shift device 123 enables boards to be transported between the ~~paths~~ unprocessed board transfer path 1211 and the process-finished board transfer path 1221, the need of setting a new mounting line for mounting ~~the~~ remaining components is eliminated.  
20 Further, even when ~~the~~ a printed board to be produced is to be changed, the board transfer units 121, 122 of the component mounting apparatus of the first embodiment can be used by changing types of components to be mounted by each component supply/mounting machine 110 and by controlling ~~the~~ a board ~~move~~ movement operation ~~by~~ via the shift device 123.

[00107] Accordingly, ~~the~~ production efficiency can be improved in accordance with kinds

of boards to be produced without greatly changing a layout in a factory, including a layout of ~~the~~  
a board production line, incidental facilities, etc and the like.

[00108] Fig. 8 shows a constitution in which, for ~~the-a~~ case where all electronic  
 components to be mounted to a printed board to be produced are not mounted by one component  
 5 mounting apparatus, six component mounting apparatuses 101-1 to 101-6 are aligned in series  
 along ~~the~~ transfer direction 124 so that ~~the-three~~ component mounting apparatuses 101-1 to 101-  
 3 of ~~the-an~~ upstream side mount equal components while ~~the-component~~ mounting apparatuses  
 101-4 to 101-6 of ~~the-a~~ downstream ~~down-stream~~ side mount equal components, and one shift  
 device 123 is arranged only between ~~the-component~~ mounting apparatus 101-3 and ~~the~~  
 10 component mounting apparatus 101-4. The component mounting apparatuses 101-1 to 101-3  
 and the component mounting apparatuses 101-4 to 101-6 mount different components ~~from~~  
relative to each other. Each of the component mounting apparatuses 101-1 to 101-3 mounts part  
 of all ~~the-components~~, and each of the component mounting apparatuses 101-4 to 101-6 mounts  
~~the-rest~~ a remainder of the components.

[00109] In the above constitution, a first unmounted board 7 to a third unmounted board 7  
 transferred along ~~the-unprocessed~~ board transfer path 1211 are sequentially supplied to ~~the~~  
 component supply/mounting machines 110-1 to 110-3, respectively. Each of mounted boards 8  
 having components mounted by the component supply/mounting machines 110-1 to 110-3  
 respectively is sequentially carried out to ~~the-process-finished~~ board transfer path 1221. In this  
 20 example, three mounted boards 8 are moved by the shift device 123 at a time from the process-  
 finished board transfer path 1221 to the unprocessed board transfer path 1211. The three  
 mounted boards 8 carried to the unprocessed board transfer path 1211 are sequentially supplied  
 to ~~the-component~~ supply/mounting machines 110-4 to 110-6 of the component mounting  
 apparatuses 101-4 to 101-6, respectively, and ~~the-a~~ mounting operation is ~~carried-out~~ performed

by each of the component mounting apparatuses 101-4 to 101-6. Upon completion of ~~the~~these mounting operations, finished printed boards are sequentially sent out from the component supply/mounting machines 110-4 to 110-6 to the process-finished board transfer path 1221 and transferred along the process-finished board transfer path 1221 to ~~the~~a next process.

5     **[00110]**     The above-referred case, that all electronic components to be mounted to a printed board to be produced are not completely mounted by one component mounting apparatus, corresponds not only to a case where it is impossible to have ~~the~~ component supply part 1121 ~~that can~~ supply necessary components for producing one printed board in one component mounting apparatus 101, but also to a case where different electronic components are only partly  
 10     used and common electronic components are used for ~~the~~a remaining part ~~in the~~of boards for, e.g., models of portable phones, personal computers or the like. In such case as above when only part of the electronic components are different, the common electronic components are mounted, for example, by a plurality of component mounting apparatuses 101 arranged, e.g., at the upstream side, then common electronic component-mounted boards 8 are moved by the shift  
 15     device 123 from the process-finished board transfer path 1221 to the unprocessed board transfer path 1211, so that different electronic components are mounted by, e.g., a plurality of component mounting apparatuses 101 arranged, e.g., at the ~~down-stream~~downstream side, respectively. Boards in conformity with each model can thus be produced and ~~the~~a need of setting production lines each corresponding to printed boards of each model is eliminated.

20     **[00111]**     According to the board transferring apparatus and the component mounting apparatus with the board transferring apparatus of the first embodiment as above, when a plurality of component mounting apparatuses 101 are arranged, it can meet various forms of production from when each of the component mounting apparatuses 101 mounts all components to each unmounted board 7 to when each of the component mounting apparatuses 101 mutually

mounts different components. In other words, by storing into the controller 180 a processing program based on types and ~~the number~~ an amount of components to be mounted by the component mounting apparatuses 101 arranged along the transfer direction 124, a setting position of the shift device 123 and ~~the a production form carried out to~~ performed for the boards, the controller 180 can control ~~the operation~~ of the unprocessed board transfer unit 121, the process-finished board transfer unit 122 and the shift device 123, so that it can meet the above various forms of production.

[00112] As discussed hereinabove, according to the board transferring apparatus, the board transfer method ~~carried out~~ performed by the board transferring apparatus, and the component mounting apparatus having the board transferring apparatus of the first embodiment, since the shift device 123 is included, various forms of production can be met as described above in ~~an equal~~ a space equal to a space occupied by a component mounting apparatus including the unprocessed board transfer path 1211 and the process-finished board transfer path 1221 and disclosed in the published application of JP,10-256785,A. ~~The A layout in the a factory,~~ including ~~the a layout of the a board production line and incidental equipment, etc. and the like~~ is not necessary to ~~change~~ be changed substantially.

[00113] ~~The furnishing Provision~~ of the shift device 123 can improve the production efficiency in accordance with kinds of boards to be produced, as described above.

[00114] The foregoing description is based on ~~that the unmounted boards 7 transferred from a previous process of the component mounting apparatus 101, 102 are being identical ones to one another.~~ As in Figs. 7 and 8, when ~~the a plurality of component mounting apparatuses 101 are arranged along the transfer direction 124 to mount components, it is hard to determine by which of the component supply/mounting machines 110 each of the mounted boards 8, sent out from the a mounting process, is to have components mounted thereto.~~ Therefore, for example,

when mounting failures frequently ~~take place~~ occur, it is difficult to specify the component supply/mounting machine 110 causing ~~the a~~ mounting failure.

[00115] As such, each component mounting apparatus may have a mark application device, which has a different mark in correspondence to each component mounting apparatus, for applying ~~the a~~ mark to ~~the~~ mounted boards 8. In this arrangement, the mark application device can apply ~~the a~~ mark, specific to ~~the a~~ component mounting apparatus, to ~~the a~~ mounted board 8 before the board is carried into ~~the a~~ component mounting apparatus of ~~the a~~ next stage after being sent out by the process-finished board send-out device 1222 to the process-finished board transfer path 1221. ~~The A~~ component mounting apparatus causing ~~the a~~ mounting failure can be specified accordingly, for instance, by confirming the mark applied ~~on to~~ the mounted board 8 with the mounting failure.

[00116] As described above, although the first embodiment is based on ~~that the~~ unmounted boards 7 transferred from ~~the a~~ previous process of the component mounting apparatus 101, 102 ~~are being~~ identical ~~ones~~ to one another, the embodiment is not limited to this. For example, boards of different kinds, because of a difference of, e.g., a board size, components mounted beforehand, ~~etc. and the like~~ can be transferred from ~~the a~~ previous process. The controller 180 controls ~~the~~ operation of the unprocessed board carry-in device 1212 and the shift device 123 in this constitution alike, so that boards can be supplied to ~~the~~ component mounting apparatuses corresponding to kinds of boards to complete target mounted boards 8.

[00117] While ~~the an operational operation control to of~~ the shift device 123 is ~~carried out~~ performed in accordance with ~~the a~~ mounting program stored in the controller 180 in the above first embodiment, ~~the~~ control is not limited to this. For example, a detector may be installed before the shift device 123 in the transfer direction 124. The detector detects an information part which is formed by, e.g., a bar code or the like, attached to ~~the a~~ transferred board 8, 7, and has

information ~~on the~~ of operational ~~operation~~ control for the shift device 123, thereby controlling the operation of the shift device 123.

[00118] The component mounting apparatus is depicted as an example of the ~~component-mounted~~ component-mounted board production apparatus in the above-described first embodiment. In ~~the~~ a case, for instance, of ~~the~~ a printing apparatus for printing the solder paste to boards, the following arrangement and operation can be devised, for example. Concretely, the printing apparatuses with respective masks ~~in~~ of different size ~~sizes~~ are provided, and boards of different sizes corresponding to the respective masks are sequentially transferred. The shift device 123 is controlled in operation so that each board is supplied to ~~the~~ a printing apparatus having ~~the~~ a proper mask.

## SECOND EMBODIMENT

[00119] Fig. 10 shows a component mounting apparatus 201 provided with a board transferring apparatus 221 in ~~the present~~ a second embodiment, and ~~including~~ includes a component supply/mounting machine 210 for receiving an unmounted board 7 from the board transferring apparatus 221, mounting electronic components onto this board and sending out an electronic component-mounted board 8 to the board transferring apparatus 221 after ~~the~~ this mounting, and a controller 280 for controlling operation of the board transferring apparatus 221 and the component supply/mounting machine 210. According to the present second embodiment, the above unmounted board 7 corresponds to an example of ~~the~~ unprocessed boards before being processed by the component-mounted board production apparatus and, the mounted board 8 corresponds to an example of ~~the~~ process-finished boards after being processed by the component-mounted board production apparatus. There are included for the unmounted board 7 one case in which one circuit exerting one function is formed ~~to~~ on the board, and ~~the other~~

another case in which a plurality of circuits each exerting the same function are formed ~~to~~ on the board.

[00120] Although the controller 280 is illustrated in Fig. 10 ~~and the like~~ to be separately arranged from the component mounting apparatus, the controller may be arranged inside the component mounting apparatus or may be arranged for each part constituting the component mounting apparatus.

[00121] The component supply/mounting machine 210 is of a high-speed machine type of ~~the~~ a so-called rotary form and includes, as shown in Fig. 12, a component hold/mounting unit 211, a component supply unit 212 for supplying electronic components to the component hold/mounting unit 211, an XY-table 213 movable in mutually orthogonal XY-directions where unmounted boards 7 are loaded, and a board supply/send unit 214 for supplying ~~the~~ an unmounted board 7 to the XY-table 213 and sending out the unmounted board 7 from the XY-table 213.

[00122] The component hold/mounting unit 211 has a rotating device 2111 and a rotary part 2112 intermittently rotatable by ~~every~~ a predetermined angle ~~by~~ via the rotating device 2111, with ~~having~~ a plurality of component hold/lift parts 2113 being arranged at ~~the~~ a periphery of the rotary part 2112 at equal intervals to be movable up and down. The component hold/lift parts 2113 have component hold members 2114 attached to leading ends thereof for holding electronic components, e.g., by suction. The component hold/mounting unit 211 constituted as described above ~~can not~~ cannot move in the XY-directions.

[00123] The component supply unit 212 has component supply parts 2121 and a moving device 2122. The component supply parts have reels 2123 set for each kind of electronic components 215. Tapes with the electronic components 215 stored therein are wound ~~to~~ the about respective reels. The component supply parts let off ~~the~~ tapes from ~~the~~ respective reels



2123, thereby supplying electronic components 215. The moving device 2122 to which the component supply parts 2121 are secured moves the component supply parts 2121 in the X-direction so as to make the component hold/mounting unit 211 hold desired electronic component 215. Although two component supply units 212 are arranged in the present second embodiment, the number is not limited to this.

[00124] The board supply/send unit 214 has a board transfer passage 2141 and a driving device 2142 for transferring ~~the-an~~ unmounted board 7 and mounted board 8 along the board transfer passage 2141. The board transfer passage 2141, which is a passage extending in parallel along a transfer direction 224 of the unmounted board 7 and mounted board 8, is formed of a fixed side rail 225 and a movable side rail 226 and can be fitted to boards 7, 8 of various sizes by moving the movable side rail 226 in a breadth direction of boards 7, 8. The fixed side rail 225 and the movable side rail 226 are provided with belt conveyors capable of supporting opposite side edge portions of the boards 7, 8. The boards 7, 8 are transferred in the aforementioned transfer direction 224 by driving each belt conveyor by a the driving device 2142 ~~for transfer~~.

[00125] Each of the above-described component hold/mounting unit 211, the component supply unit 212, the XY-table 213 and the board supply/send unit 214 is connected to the controller 280 to be controlled in operation by the controller 280.

[00126] In the component supply/mounting machine 210 of the above constitution, electronic components 215 are supplied and mounted by operations as will be described below.

~~In the first place~~Initially, ~~the-an~~ unmounted board 7 is placed on the XY-table 213 by the board supply/send unit 214, the unmounted board 7 is moved to below the rotary part 2112 by the XY-table 213 and is positioned so that a mounting preparation position of the rotary part 2112 agrees with a mounting position on the unmounted board 7. Meanwhile, the component supply part 2121 which is to supply ~~the-a~~ desired electronic component 215 is positioned by the moving

device 2122 to a component hold position where the component hold member 2114 is to hold the electronic component 215 received from the component supply part 2121, and the component hold/lift part 2113 moves down to hold the electronic component 215 by the component hold member 2114. After ~~the~~ this holding, the component hold/lift part 2113 moves up and the rotary part 2112 is rotated by the rotating device 2111, thereby disposing the component hold/lift part 2113 to the mounting preparation position for mounting the held electronic component 215 to the board 7. Next, the component hold/lift part 2113 is moved down to mount the electronic component 215 to the mounting position on the board 7. After ~~the~~ this mounting, the component hold/lift part 2113 moves up and is arranged ~~to~~ at the component hold position again by the rotation of the rotary part 2112.

[00127] Electronic components 215 are sequentially mounted onto the unmounted board 7 by component hold members 2114 through a repetition of the above-described operation.

[00128] According to the present second embodiment, the component supply/mounting machine 210 is ~~the~~ a high-speed machine type of the so-called rotary form. However, the machine is not limited to ~~the~~ this type, and various known component supply/mounting machines such as a so-called ~~multifunction~~ multi-function type in which, for example, a mounting head part with ~~the~~ component hold members 2114 is freely movable in ~~the~~ XY-directions and can supply components also from trays, or the like, may be adopted.

[00129] Hereinbelow will be described the above-mentioned board transferring apparatus 221.

[00130] The board transferring apparatus 221 has one board transfer path 2211 for transferring ~~the~~ an unmounted board 7, to be processed by the above described component supply/mounting machine 210, and ~~the~~ a mounted board 8 processed by the ~~above~~ component supply/mounting machine 210. Moreover, the board transferring apparatus includes a board

carry-in device 2212 which moves between the board transfer path 2211 and the component supply/mounting machine 210, thereby carrying ~~the-an~~ unmounted board 7 to the component supply/mounting machine 210, and further includes a board send-out device 2222 which moves between the board transfer path 2211 and the component supply/mounting machine 210, thereby sending out ~~the-a~~ mounted board 8 from the component supply/mounting machine 210 to the board transfer path 2211. The board transferring apparatus also includes an identifying device 2215 disposed at the board transfer path 2211 for recognizing carry-in propriety display parts 2216 on the boards 7, 8, which represent whether or not the unmounted board 7 and the mounted board 8 can be sent into the component supply/mounting machine 210, and also includes the controller 280 for controlling operations of the board carry-in device 2212, the board send-out device 2222 and the identifying device 2215, and also judging whether or not the boards 7, 8 are to be carried into the component supply/mounting machine 210 by controlling operation of the board carry-in device 2212 based on an identification result obtained by identifying the carry-in propriety display part 2216 by the identifying device 2215.

[00131] The board transfer path 2211 is constituted of a fixed side rail 225 and a movable side rail 226 extending parallel along the transfer direction 224 of ~~the-unmounted~~ board 7 and mounted board 8, functioning as a bypass line of the board transfer passage 2141. The board transfer path 2211 can be conformed to unmounted boards 7 and mounted boards 8 of various sizes by moving the movable side rail 226 in ~~the-a~~ breadth direction of the boards 7 and 8. Belt conveyors capable of supporting opposite side edge portions of ~~the-an~~ unmounted board 7 and ~~the-mounted~~ board 8 are equipped to each of the fixed side rail 225 and the movable side rail 226. The unmounted board 7 and mounted board 8 are transferred in the above transfer direction 224 by driving each of the conveyors by a driving device 2213 ~~for transferring boards~~.

[00132] The board carry-in device 2212 has, as shown in Fig. 13, a supply side board hold

part 22121 and a drive part 22122. As indicated in Figs. 11 and 13, since the board transfer path 2211 and the board transfer passage 2141 are arranged to be an equal height in the second embodiment, the drive part 22122 reciprocates the supply side board hold part 22121 between the board transfer path 2211 and the board transfer passage 2141. According to the second embodiment, a sensor 22123, for instance, a limit switch, a proximity sensor or the like, for detecting that the supply side board hold part 22121 is positioned at the board transfer path 2211, is installed, so that an arrangement position of the supply side board hold part 22121 is determined by the controller 280 based on a signal supplied from the sensor 22123 to the controller 280.

[00133] The drive part 22122 is constructed ~~in from~~ a structure ~~with including~~ a ball screw in the second embodiment, having a motor 221221 corresponding to a driving source controlled in operation by the controller 280. The supply side board hold part 22121 has the fixed side rail 225 and the movable side rail 226, thus forming part of the board transfer path 2211 when arranged at the board transfer path 2211 and forming part of the board transfer passage 2141 when arranged at the board transfer passage 2141.

[00134] The above-constituted board carry-in device 2212 operates as will be discussed below. The supply side board hold part 22121, which is normally arranged at the board transfer path 2211, holds ~~the an~~ unmounted board 7 between the fixed side rail 225 and the movable side rail 226 of the supply side board hold part 22121 when it is necessary to send ~~the this~~ transferred unmounted board 7 to the component supply/mounting machine 210, and moves the unmounted board 7 by the drive part 22122 to the board transfer passage 2141. The unmounted board 7 moved to the board transfer passage 2141 is subjected to ~~the a~~ mounting operation. In the meantime, the supply side board hold part 22121 returns to the board transfer path 2211 after sending the unmounted board 7 to the board transfer passage 2141. When it is not necessary to

carry the unmounted board 7 into the component supply/mounting machine 210, the unmounted board 7 passes the supply side board hold part 22121.

[00135] As shown in Fig. 14, the board send-out device 2222 has a discharge side board hold part 22221 and a drive part 22222. The drive part 22222 reciprocates the discharge side board hold part 22221 between the board transfer path 2211 and the board transfer passage 2141. In the present second embodiment, for instance, a sensor 22223 such as a limit switch, a proximity sensor or the like is installed to detect that the discharge side board hold part 22221 is positioned at the board transfer path 2211, and an arrangement position of the discharge side board hold part 22221 is determined by the controller 280 on ~~the~~ a basis of a signal supplied to the controller 280 from the sensor 22223.

[00136] The drive part 22222 is formed ~~in~~ from a structure ~~with~~ including a ball screw in the second embodiment, and a motor 222221 corresponding to a driving source is controlled in operation by the controller 280. The discharge side board hold part 22221 includes the fixed side rail 225 and the movable side rail 226, thereby forming part of the board transfer path 2211 when positioned at the board transfer path 2211 and forming part of the board transfer passage 2141 when positioned at the board transfer passage 2141.

[00137] The above-constituted board send-out device 2222 operates as will be ~~depicted~~ described below. The discharge side board hold part 22221 normally arranged at the board transfer path 2211 is moved by the drive part 22222 from the board transfer path 2211 to the board transfer passage 2141 when ~~the~~ a mounted board 8 is to be sent out from the component supply/mounting machine 210. After being positioned at the board transfer passage 2141, the discharge side board hold part 22221 holds the mounted board 8 between the fixed side rail 225 and the movable side rail 226 of the discharge side board hold part 22221, and then is moved from the board transfer passage 2141 to the board transfer path 2211. The mounted board 8 sent

to the board transfer path 2211 is transferred by the driving device 2213 ~~for board transfer along~~ the board transfer path 2211 in the transfer direction 224.

[00138] The identifying device 2215, which is one of ~~features-characteristic~~ feature characteristics of the board transferring apparatus 221 of the second embodiment and identifies the carry-in propriety display part 2216 on the board 7, 8 as mentioned earlier, will be described next.

[00139] ~~The carry-in~~ Carry-in propriety display part 2216 is a part indicative of supply-propriety information showing whether or not ~~the-an~~ unmounted board 7 and ~~the-a~~ mounted board 8, transferred along the board transfer path 2211, are to be sent to the component supply/mounting machine 210, and moreover indicating ~~the-component~~ supply/mounting machine 210 of the component mounting apparatuses 201 to which the unmounted board 7 and the mounted board 8 are to be supplied, for instance, when a plurality of component mounting apparatuses 201 are arranged in series along the transfer direction 224 as shown in Fig. 15. The display part 2216 is formed of a bar code in the second embodiment and attached, e.g., to an end part on a mounting face of the boards 7, 8 where electronic components 215 are mounted, as shown in Fig. 10. Form of the carry-in propriety display part 2216 is not limited to the above bar code and can be any kind of form so long as each board can be identified, for example, a geometrical shape such as a circle, a triangle, a quadrilateral or the like, a pattern of a ~~diee~~ die or the like, a board number formed ~~to the~~ on boards 7, 8, a wiring pattern, a part processed ~~part~~ by the component-mounted board production apparatus, namely, a part on the board where components are mounted according to the second embodiment, ~~ete~~ and the like. The carry-in propriety display part 2216 is preferably formed in a state in which ~~the-supply-propriety~~ information can be rewritten to cope with a change in production form to be described later, ~~ete~~ and the like. For example, an IC memory or the like is included in the carry-in propriety display

part 2216 accordingly.

[00140] As indicated in Fig. 11, the identifying device 2215 for identifying the above described carry-in propriety display part 2216 has a detect part 22151 and a determination part 22152. Since the determination part 22152 is included in the controller 280 in the constitution adopted according to the second embodiment, the detect part 22151 corresponds to the above identifying device 2215. The detect part 22151 is a device for detecting ~~the~~ carry-in propriety display part 2216 and is a generally used bar code reader using LEDs (light-emitting diode) in the second embodiment. The identifying device 2215 may have a function for rewriting ~~the~~ supply-propriety information. According to the second embodiment as indicated in Fig. 10, the detect part 22151 is arranged ~~to~~ above the supply side board hold part 22121 positioned at the board transfer path 2211, so that it can detect ~~the~~ carry-in propriety display part 2216 of the boards 7, 8 when the boards 7, 8 are disposed ~~to~~ at the carry side board hold part 22121 positioned at the board transfer path 2211. A position where to arrange the detect part 22151 is not limited to ~~the~~ that described above. The detect part 22151 may be arranged at a position before ~~the~~ boards 7, 8 are carried into the component mounting apparatus 201, for example, may be arranged ~~at~~ above a stop region 2214 so that it can detect ~~the~~ carry-in propriety display part 2216 of ~~the~~ boards 7, 8 when the boards 7, 8 are arranged ~~to~~ at the stop region 2214 formed immediately before the board carry-in device 2212 in the transfer direction 224.

[00141] The determination part 22152 decides on the basis of ~~the~~ an identification result of the carry-in propriety display part 2216, by the detect part 22151, whether or not ~~the~~ boards 7, 8 are to be carried to the component supply/mounting machine 210 and controls ~~the~~ operation of the board carry-in device 2212.

[00142] A detailed operation ~~in the~~ of a component mounting operation of the identifying device 2215 constituted as described above will be ~~depicted~~ described later.

[00143] One component mounting apparatus 201 is thus formed in the above-discussed arrangement. A modified example as will be described below can be constructed.

[00144] Specifically, as a component mounting apparatus 202 shown in Fig. 15, a plurality of component mounting apparatuses 201-1, 201-2, ... can be arranged in series in the transfer direction 224. In the second embodiment, since both the unmounted board 7 and the mounted board 8 are transferred along one board transfer path 2211, ~~when the~~ with a plurality of component mounting apparatuses 201 arranged, it is necessary to prevent the board 7 from not being ~~not~~ supplied to any of the component supply/mounting machines ~~210~~ 210-1, 210-2, ... and being carried out of the component mounting apparatus 202 without having components mounted thereto, for example, as a result of a detection error of ~~the~~ a corresponding one of identifying ~~device 2215~~ devices 2215-1, 2215-2, .... A processing part in the component-mounted board production apparatus, i.e., a recognizing device 227, which detects the presence/absence of components on ~~the~~ a board in the second embodiment, is preferably arranged corresponding to a component-mounted board production apparatus, ~~201~~ located at ~~the~~ a trail end in the transfer direction 224, from among the plurality of component mounting apparatuses ~~201~~. The recognizing device 227 is connected to the controller 280, and the controller 280 controls operation of the component mounting apparatus 201-4 ~~of~~ at the trail end based on information from the recognizing device 227.

[00145] Component mounting operation in the above-described component mounting apparatus will be described below by taking as an example ~~the~~ a component mounting apparatus 202 having four component mounting apparatuses 201-1 to 201-4 arranged in series along the transfer direction 224 as shown in Figs. 15-17. It is to be noted here that a component mounting operation ~~to the~~ for an unmounted board 7 in the component supply/mounting machine ~~210~~ of each component mounting apparatus ~~201~~ is similar to the conventional operation and will be



briefly described.

[00146] In addition, all ~~operations-performances~~ of the component mounting operation are controlled by the controller 280. In other words, a program in relation to the mounting operation, such as a relationship between the mounting positions on the unmounted board 7 and electronic components 215 to be mounted to the mounting positions, a mounting order, and the like ~~is~~are stored in the controller 280. The controller 280 controls the operation of the ~~each~~ component supply/mounting machine 210 and also controls the operations of the board transferring apparatus 221 including the board carry-in device ~~2212~~ devices 2212-1, 2212-2,... and the board send-out device ~~2222~~ devices 2222-1, 2222-2,... and, the identifying device ~~2215~~ devices 2215-1, 2215-2,....

[00147] In the following description, ~~the~~ unmounted boards 7 transferred from ~~the~~an upstream side of the component mounting apparatus 202 are identical ~~ones to each other~~, and four unmounted boards 7A, 7B, 7C, 7D are transferred in this order. A carry-in propriety display part 2216A with information, so that the unmounted board 7A is supplied to the component mounting apparatus 201-1, is attached to the unmounted board 7A; a carry-in propriety display part 2216B with information, so that the unmounted board 7B is supplied to the component mounting apparatus 201-2, is attached to the unmounted board 7B; a carry-in propriety display part 2216C with information, so that the unmounted board 7C is supplied to the component mounting apparatus 201-3, is attached to the unmounted board 7C; and a carry-in propriety display part 2216D with information, so that the unmounted board 7D is supplied to the component mounting apparatus 201-4, is attached to the unmounted board 7D.

[00148] The component mounting apparatuses 201-1 to 201-4 are constructed to mount equal components.

[00149] The first unmounted board 7A transferred on the board transfer path 2211 by the

driving device 2213, for transferring unmounted boards from the upstream side of the component mounting apparatus 202, is temporarily stopped by the supply side board hold part 22121 arranged at the board transfer path 2211 of the board carry-in device 2212-1 of the component mounting apparatus 201-1. As described before, since the controller 280 confirms ~~the~~an arrangement position of the supply side board hold part 22121 based on ~~the~~a signal from the sensor 22123, unless the supply side board hold part 22121 is positioned at the board transfer path 2211, the controller 280 controls ~~the~~ operation of the driving device 2213 ~~for board transfer~~ to stop the unmounted board 7A ~~to~~at the stop region 2214, and then ~~carries~~ the unmounted board 7A is carried to the supply side board hold part 22121 after the supply side board hold part 22121 is positioned ~~to~~at the board transfer path 2211.

[00150] After the unmounted board 7A is carried to the supply side board hold part 22121, the identifying device 2215-1 recognizes the carry-in propriety display part 2216A of the unmounted board 7A, and the controller 280 determines, based on ~~the~~ information from the carry-in propriety display part 2216A, whether or not the unmounted board 7A is to be supplied to the component mounting apparatus 201-1. In this case, ~~the~~ information of supplying the unmounted board 7A to the component mounting apparatus 201-1 is described in the carry-in propriety display part 2216A, and therefore the controller 280 controls ~~the~~ operation of the motor 221221 of the board carry-in device 2212-1 for arranging the supply side board hold part 22121 ~~to~~at the board transfer passage 2141 so as to supply the unmounted board 7A to the component mounting apparatus 201-1, and after ~~the~~this arranging, the controller 280 transfers the unmounted board 7A along the board transfer passage 2141. The supply side board hold part 22121 returns to the board transfer path 2211 after the unmounted board 7A is carried to the board transfer passage 2141.

[00151] The unmounted board 7A is transferred along the board transfer passage 2141 to

the XY-table 213 arranged ~~to~~at the board transfer passage 2141, placed on the XY-table 213, positioned to a predetermined position and held. After the board is held to the XY-table 213, the XY-table 213 is arranged ~~to~~below the component hold/mounting unit 211. After ~~the~~this arrangement, ~~the~~an electronic component 215 is mounted onto the unmounted board 7A by the component supply/mounting machine ~~210~~210-1 as described earlier. More specifically, the unmounted board 7A on the XY-table 213 is positioned so that ~~the~~a mounting position on the unmounted board 7A agrees with ~~the~~a mounting preparation position of ~~the~~ rotary part 2112, and at the same time, ~~the~~ component supply part 2121 is positioned by ~~the~~ moving device 2122 to the component hold position where ~~the~~ component hold member 2114 is to hold the electronic component 215 received from the component supply part 2121. After the component hold member 2114 holds the electronic component 215 at the component hold position, the rotary part 2112 rotates to the mounting preparation position, whereby the electronic component 215 is mounted to the mounting position of the unmounted board 7A. The component hold member 2114 moves up after ~~the~~this mounting and is arranged ~~to~~at the component hold position again through ~~the~~ rotation of the rotary part 2112. Electronic components 215 are sequentially mounted to respective mounting positions on the unmounted board 7A by ~~the~~ component hold members 2114 of the rotary part 2112 in this manner.

**[00152]** On the other hand, while the electronic components 215 are mounted onto the unmounted board 7A, boards 7B, 7C, 7D are sequentially temporarily stopped by the supply side board hold part 22121 of the component mounting apparatus 201-1, and the carry-in propriety display parts 2216B, 2216C, 2216D are recognized by the recognizing device 2215-1. Since the carry-in propriety display parts 2216B, 2216C, 2216D do not include ~~the~~ information of ordering ~~the~~ supply to the component mounting apparatus 201-1, each of the unmounted boards 7B, 7C, 7D is determined as not to be taken into the component mounting apparatus 201-1, and is carried

to the component mounting apparatus ~~201-1~~ 201-2 by being passed ~~passing~~ along the board transfer path 2211 through the supply side board hold part 22121, the discharge side board hold part 22221 of the component mounting apparatus 201-1, and a path 2217-1 for connection.

[00153] Similar to the earlier-described supply and mounting operation for the unmounted board 7A ~~to~~ at the component mounting apparatus 201-1, the unmounted board 7B is permitted to be supplied to the component supply/mounting machine 210-2 of the component mounting apparatus 201-2 through ~~the~~ a recognition operation performed by the recognizing device 2215-2 included in the component mounting apparatus 201-2, and subjected to ~~the~~ a mounting operation by the component supply/mounting machine 210-2. The unmounted board 7C is permitted to be supplied to the component supply/mounting machine 210-3 of the component mounting apparatus 201-3 by ~~the~~ a recognition operation of the recognizing device 2215-3 of the component mounting apparatus 201-3, and subjected to a mounting operation by the component supply/mounting machine 210-3. For the unmounted board 7D, ~~the~~ supply to the component supply/mounting machine 210-4 of the component mounting apparatus 201-4 is permitted by ~~the~~ a recognition operation of the recognizing device 2215-4 of the component mounting apparatus 201-4, so that components are mounted to board 7D by the component supply/mounting machine 210-4.

[00154] In the meantime, ~~the~~ mounted board 8A<sub>1</sub> formed by mounting all of predetermined electronic components 215 to the unmounted board 7A<sub>1</sub> is ~~taken out~~ transferred from the XY-table 213 to ~~the~~ board supply/send unit 214, further sent to ~~the~~ discharge side board hold part 22221, arranged ~~to~~ at the board transfer passage 2141, of ~~the~~ board send-out device 2222-1 of the component mounting apparatus 201-1, and then held by the discharge side board hold part 22221. ~~The~~ This mounted board is then returned to the board transfer path 2211 by the discharge side board hold part 22221.

[00155] While the unmounted boards 7B, 7C, 7D are transferred along the board transfer path 2211 as described above, the controller 280 controls ~~the~~a transfer operation for each board so as to prevent interference of ~~the~~ transfer of the unmounted boards 7B, 7C, 7D with ~~the~~ transfer of the mounted board 8A, and to be able to shorten a Tact. For example, a state is shown in Fig. 15 in which, during the mounting operation ~~to~~of the unmounted board 7A performed by the component mounting apparatus 201-1, the unmounted board 7B is supplied to the component supply/mounting machine 210-2 of the component mounting apparatus 201-2, the unmounted board 7C is disposed ~~to~~at the discharge side board hold part 22221 of the board send-out device 2222-1 of the component mounting apparatus 201-1, and the unmounted board 7D is arranged ~~to~~at the supply side board hold part 22121 of the board carry-in device 2212-1 of the component mounting apparatus 201-1.

[00156] The controller 280 determines that it is possible to supply a next unmounted board 7 to the component supply/mounting machine 210-1 on ~~the~~a basis of factors such ~~that the~~as boards 7, 8 ~~are~~being absent ~~on~~from the XY-table 213, the component supply/mounting machine 210-1 ~~is~~being at rest, or the like.

[00157] Fig. 16 indicates a state wherein the mounted board 8A is arranged ~~to~~on the board transfer path 2211 while held ~~to~~by the discharge side board hold part 22221 of the component mounting apparatus 201-1, ~~whereas~~while the unmounted board 7B is being subjected to ~~the~~a mounting operation performed by the component supply/mounting machine 210-2 of the component mounting apparatus 201-2, and the unmounted board 7C is in the middle of ~~the~~a mounting operation performed by the component supply/mounting machine 210-3 of the component mounting apparatus 201-3, with the unmounted board 7D being arranged ~~to~~at the supply side board hold part 22121 of the board carry-in device 2212-4 of the component mounting apparatus 201-4.

[00158] Fig. 17 represents a state in which the mounted board 8A is transferred to the discharge side board hold part 22221 of the board send-out device 2222-4 of the component mounting apparatus 201-4, and the mounted board 8B is transferred to the stop region 2214 located immediately before the board send-out device 2222-4 of the component mounting apparatus 201-3, ~~whereas~~ while the unmounted board 7C is being subjected to ~~the~~ a mounting operation by the component supply/mounting machine 210-3 of the component mounting apparatus 201-3 and the unmounted board 7D is being subjected to ~~the~~ a mounting operation by the component supply/mounting machine 210-4 of the component mounting apparatus 201-4.

[00159] As is shown in Fig. 17, when ~~the~~ a mounted board is transferred and temporarily stopped ~~to~~ at the discharge side board hold part 22221 of the board send-out device 2222-4 of the component mounting apparatus 201-4, ~~the~~ presence/absence of ~~the~~ mounted components is detected by the recognizing device 227 in addition to ~~the~~ an identification operation performed by the identifying device 2215-4. When the controller 280 determines ~~the~~ presence of the mounted components based on output information of the recognizing device 227, this board is directly transferred to ~~the~~ a next process along the board transfer path 2211 in the transfer direction 224. The next process is, for example, a soldering process or the like. In contrast, when ~~the~~ an absence of ~~the~~ a mounted component is decided, the controller 280 controls the operation of each part so as to supply the board, determined to have no component, to the component supply/mounting machine 210-4 of the component mounting apparatus 201-4 and ~~mount~~ have components mounted to the board because the component mounting apparatuses 201-1 to 201-4 are designed to mount equal components in the present second embodiment as mentioned before.

[00160] Similar to the above-described mounted board 8A, ~~the~~ presence/absence of the mounted components is detected for the mounted boards 8B, 8C by the recognizing device 227,

and operation based on ~~the~~this detected result is ~~carried out~~ performed.

[00161] As discussed hereinabove, in the component mounting apparatus 202 with the board transferring apparatus 221 of the second embodiment, when ~~the~~a plurality of component supply/mounting machines 210 are arranged along the transfer direction 224, and moreover each of the component supply/mounting machines 210 mounts all components necessary for one complete board, a necessary time for loading ~~the~~ boards 7 to each of the component supply/mounting machines 210 is a time for loading one board to one component supply/mounting ~~machines~~ machine 210 irrespective of the number of the component supply/mounting machines 210. A production time per board can be accordingly shortened and a production efficiency of the component mounting apparatus can be improved. The embodiment ~~goes~~is the same as the conventional component mounting apparatus of Fig. 9 from this view point. However, the conventional component mounting apparatus requires two paths for transferring ~~the~~ boards 7, 8 as a bypass route of ~~the~~ board transfer passage 2141 in the component supply/mounting machine 210. In contrast, one board transfer path 2211 is ~~enough~~ sufficient in the component mounting apparatus of the present second embodiment, thereby enabling curtailing an apparatus constitution, an apparatus cost, etc and the like.

[00162] Furthermore, in the component mounting apparatus 201, 202 having the board transferring apparatus 221 of the second embodiment, as compared with the conventional component mounting apparatus shown in Fig. 9, special effects as follows can be exhibited.

[00163] Each of ~~the~~ boards 7, 8 has ~~the~~ carry-in propriety display part 2216 applied thereto, so that the component mounting apparatus 201 to which the board is supplied is specified. Therefore, for example, the component mounting apparatus 201 which mounts ~~the~~ components to ~~the~~ mounted board 8 including a mounting failure can be specified.

[00164] According to the present second embodiment, the component mounting apparatus

201 arranged ~~to~~ at the trail end is equipped with the recognizing device 227, so that ~~the~~ board 7 without components mounted thereto due to, e.g., a machine trouble, an identification error at the identifying device 2215 or the like can be detected. An error of transferring ~~the~~ unmounted board 7 to ~~the~~ a next process ~~of the~~ at a down-stream side can hence be prevented.

5 [00165] In the event that all components necessary for one complete board cannot be mounted by one component mounting apparatus 201, for example, even when part of the electronic components are mounted by the component mounting apparatuses 201-1, 201-2 and ~~the~~ remaining electronic components are mounted by the component mounting apparatuses 201-3, 201-4, thereby finishing one printed board in the component mounting apparatus 202 shown in  
10 Fig. 15, it is possible to produce ~~the~~ a finished board in the above board transfer path 2211 without constructing a fresh mounting line. Moreover, even if boards to be produced change, ~~the~~ production efficiency can be improved in accordance with types of boards to be produced without greatly changing ~~the~~ a layout in ~~the~~ a factory, including ~~the~~ a layout of ~~the~~ a board production line, incidental facilities, ~~etc. and the like~~, which will be discussed in detail below.

15 [00166] In ~~the~~ a case of mounting part of electronic components by the component mounting apparatuses 201-1, 201-2 and mounting ~~the rest of~~ remaining electronic components by the component mounting apparatuses 201-3, 201-4 to complete one printed board, the following operation is ~~carried out~~ performed given that ~~the~~ carry-in propriety display part 2216A of ~~the~~ unmounted board 7A has information that the unmounted board 7A can be supplied to  
20 each of the component supply/mounting machines 210-1, 210-3 of the component mounting apparatuses 201-1, 201-3, while ~~the~~ carry-in propriety display part 2216B of ~~the~~ unmounted board 7B includes information that the unmounted board 7B can be supplied to each of component supply/mounting machines 210-2, 210-4 of the component mounting apparatuses 201-2, 201-4.



[00167] ~~In the~~ With this arrangement, the carry-in propriety display part 2216A of the unmounted board 7A transferred along the transfer path 2211 is identified by the identifying device 2215-1 of the component mounting apparatus 201-1 as described before, whereby the supply of board 7A to the component supply/mounting machine 210-1 is permitted on ~~the a~~ a basis of ~~the this~~ this identified result. The unmounted board 7A is subjected to mounting by the component supply/mounting machine 210-1. During ~~the this~~ this mounting operation ~~to of~~ of the unmounted board 7A, the carry-in propriety display part 2216B of the unmounted board 7B is identified by the identifying device 2215-2 of the component mounting apparatus 201-2, and the supply of board 7B to the component supply/mounting machine 210-2 is permitted on ~~the a~~ a basis of ~~the this~~ this identified result. The mounting operation ~~to of~~ of the unmounted board 7B is ~~carried out~~ performed by the component supply/mounting machine 210-2.

[00168] ~~The mounted~~ Mounted board 8A produced by the mounting operation ~~to of~~ of the unmounted board 7A in the component supply/mounting machine 210-1 is returned by the board carry-in device 2222-1 to the transfer path 2211 and transferred along the board transfer path 2211 in the transfer direction 224. ~~The information~~ Information described ~~to in~~ in the carry-in propriety display part 2216A of the mounted board 8A is not ~~the information~~ information permitting the supply thereof to the component supply/mounting machine 210-2 of the component mounting apparatus 201-2, and consequently the mounted board 8A passes the component mounting apparatus 201-2 so as to be transferred to the supply side board hold part 22121 of the component mounting apparatus 201-3. The carry-in propriety display part 2216A is identified by the identifying device 2215-3 of the component mounting apparatus 201-3, and ~~the supply of~~ the mounted board 8A to the component supply/mounting machine 210-3 is permitted on ~~the a~~ a basis of ~~the this~~ this identified result. Remaining components are mounted to the mounted board 8A by the component supply/mounting machine 210-3.

[00169] The same control operation as for the above-described mounted board 8A is executed ~~to the~~ for mounted board 8B produced by a mounting operation ~~to of~~ the unmounted board 7B performed by the component supply/mounting machine 210-2, whereby ~~the~~ remaining components are mounted to the mounted board 8B by the component supply/mounting machine 210-4 of the component mounting apparatus 201-4.

[00170] After the mounting operation ~~to of~~ the mounted board 8A in the component supply/mounting machine 210-3 and the mounting operation ~~to of~~ the mounted board 8B in the component supply/mounting machine 210-4 are respectively finished, each mounted board 8A, 8B is returned to the board transfer path 2211 and is transferred along the board transfer path 2211 in the transfer direction 224 so as to be supplied to ~~the a~~ next process.

[00171] Since ~~the~~ supply propriety to the component supply/mounting machine 210 is identified for each of ~~the~~ transferred boards 7, 8 by the identifying device 2215 as described above, there is no need of constructing a fresh mounting line to mount ~~the~~ remaining components. Moreover, even if printed boards to be produced vary, the component mounting apparatus 202 of the present second embodiment can be used by changing ~~the a~~ type of components to be mounted by each component supply/mounting machine 210, and by changing ~~the~~ supply-propriety information ~~to of~~ the component mount/setting machine 210 which is described ~~to in~~ each carry-in propriety display part 2216 of ~~the~~ board 7. In other words, ~~the~~ information ~~on of~~ supply propriety ~~to of~~ the component supply/mounting machine 210 which is described ~~to in~~ each carry-in propriety display part 2216 of each board 7 is designed to conform with ~~the a~~ mounting program stored in the controller 280 based on the constitution of the component mounting apparatus and ~~the a~~ number of electronic components to be mounted.

[00172] According to the board transferring apparatus 221 of the present second embodiment as discussed hereinabove, ~~the~~ production efficiency can be improved in accordance

with types of boards to be produced without greatly changing ~~the a~~ layout in ~~the a~~ factory, including ~~the a~~ layout of ~~the a~~ board production line and incidental facilities, ~~etc~~ and the like.

[00173] The above-described case, that all of ~~the~~ electronic components to be mounted to ~~the a~~ printed board to be produced are not completely mounted by one component mounting apparatus, corresponds not only to ~~the a~~ case where one component mounting apparatus 201 cannot have the number of component supply parts 2121 which supply components of a necessary number to form one printed board, but also to ~~the a~~ case where different electronic components are used only partly and common electronic components are used for ~~the rest a remainder~~ among models of boards, for instance, for portable phones, personal computers, ~~etc~~ and the like. When only part of the electronic components are different, common electronic components are mounted, e.g., by a plurality of component mounting apparatuses 201 arranged, e.g., ~~to the at an~~ upstream side, thereby forming mounted boards 8 ~~with including~~ the common electronic components. Then the mounted boards 8 are transferred to, e.g., a plurality of component mounting apparatuses 201 disposed ~~to the at a~~ downstream side, where each of the supply properties, of ~~to the~~ component supply/mounting machines 210 included in the respective component mounting apparatuses 201, is determined with ~~the use of~~ the identifying devices 2215. Therefore, different electronic components can be mounted in conformity with target models, so that boards conforming to each model can be produced. ~~The A~~ need of constructing a production line corresponding to each model of ~~the~~ printed boards is eliminated.

[00174] According to the board transferring apparatus 221 of this second embodiment, and the component mounting apparatus ~~with including~~ the board transferring apparatus, when a plurality of component mounting apparatuses are arranged, ~~this can cope~~ coped with can be various production forms from ~~the a~~ case where each of the component mounting apparatuses 201 mounts all components to each unmounted board 7 to ~~the a~~ case where the component

mounting apparatuses 201 mount mutually different components. That is, ~~the~~ controller 280 is enabled to control ~~the~~ operation of ~~the~~ board transferring apparatuses 221 and ~~the~~ board carry-in devices 2212 to meet various production forms by designing ~~the~~ supply-propriety information for ~~the~~ component supply/mounting machines 210, which are described ~~to~~ in carry-in propriety display parts 2216 of ~~the~~ respective boards 7, 8 on ~~the~~ a basis of a processing program which is ~~carried out~~ performed by the controller 280 according to ~~the~~ types and ~~the~~ number of components to be mounted by the component mounting apparatuses 201 arranged along the transfer direction 224, and ~~the~~ production forms ~~to~~ of these boards.

[00175] Although unmounted boards 7 transferred from ~~the~~ an upstream side are equal ones as described above in the second embodiment, ~~the~~ boards are not limited to this. Particularly, when a plurality of kinds of boards, e.g., four kinds of boards 7 are sequentially repeatedly transferred, ~~the~~ a number of produced printed boards to be stocked can be made proper. ~~Supposed~~ Suppose that one appliance needs, for example, four kinds of printed boards A-D, in the conventional component mounting apparatus of Fig. 9, boards should be produced for every kind of ~~boards~~ board because the conventional apparatus cannot produce a plurality of kinds of boards in a mixed condition. Therefore, in order for manufacturing, e.g., 100 units of the appliance, 100 pieces of board "A" should be produced first, 100 pieces of board "B" should be produced next, and so on. In other words, a necessary number of boards should be produced sequentially for each kind.

[00176] On the other hand, in the component mounting apparatus of the present second embodiment, since ~~the~~ boards A-D can be transferred in turn and supplied to ~~the~~ respective component supply/mounting machines and then subjected to ~~the~~ mounting ~~operation~~ operations, it is possible to produce in groups of boards A-D, that is, boards for every one set of the appliance can be produced. Thus, a ~~the~~ number of printed boards to be stocked can be controlled

to be proper as mentioned above.

[00177] In the embodiments shown in Figs. 15-17, both the identifying device 2215 and the recognizing device 227 are equipped with the component mounting apparatus 201-4 arranged to ~~the~~ at a trail end. However, the arrangement is not limited to this, and only the identifying device 2215 may be ~~equipped with~~ provided.

[00178] In the above second embodiment, ~~the~~ transferred boards 7, 8 are temporarily stopped when ~~the~~ carry-in propriety display part 2216 is identified by the identifying device 2215. However, ~~the~~ this identifying operation can be ~~carried out~~ performed without stopping the boards 7, 8 by equipping a different type of identifying device 2215, a moving mechanism for the identifying device 2215, or the like.

[00179] Although the present invention has been fully described in connection with the preferred embodiments thereof with reference to the accompanying drawings, it is to be noted that various changes and modifications are apparent to those skilled in the art. Such changes and modifications are to be understood as included within the scope of the present invention as defined by the appended claims unless they depart therefrom.

**BEST AVAILABLE COPY**

**ABSTRACT OF THE DISCLOSURE**

The present invention has for its object to provide an apparatus and a method for transferring boards, and a component mounting apparatus whereby a production efficiency can be improved in accordance with types of boards to be produced. For accomplishing ~~the objective~~ this object, there are arranged a shift device capable of moving a mounted board from a process-finished board transfer path to an unprocessed board transfer path, a controller for controlling ~~the~~ this moving, and ~~further~~ an identifying device. ~~The~~ This arrangement enables switching ~~the~~ of a method of transferring boards in accordance with types of boards to be produced, and controlling ~~the supply of board~~ boards to the component mounting apparatus, so that ~~the~~ production efficiency is improved in accordance with types of boards.

**BEST AVAILABLE COPY**